

Product data sheet

Specifications



ASCO 6045 Load Bank

ASCOLBLV6045

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Capacity Rating 50...100 kVA

Capacitance Rating 0.8 pF

Load Step Resolution 1 kW
1 kvar

Voltage Rating 380...690 V AC 50/60 Hz

Resistor Load Tolerance 2.5 %

Inductor Load Tolerance 3 %

Provided Equipment 1 gland plate inside the enclosure
HRC fuse inside the enclosure
Voltage transformer 1 inside the enclosure
Cooling fans inside the enclosure

Connection Terminals Terminals neutral)

IP Protection IP1x
IP2X
IP54

Enclosure Material Zintec
Aluminium
Steel

Color Gray RAL 7042)

Length 53.7 in (1364 mm)

Width 46.5 in (1180 mm)

Height 65.0 in (1650 mm)

Product Weight 2204.6 lb(US) (1000 kg)

Environmental

Standards ISO 9001
CE
IEC 60309-2

Packing Units

Unit Type of Package 1 PCE

Nbr. of units in pkg. 1

Package 1 Height 53.7 in (136.4 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Width	46.5 in (118.0 cm)
Package 1 Length	65.0 in (165.0 cm)
Package weight(Lbs)	2204.6 lb(US) (1000.0 kg)

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

Use Longer



Lifetime extension

Repair	No
--------	----