

# Product datasheet

Specifications



## iPF65r modular surge arrester - 4 poles - 340V - with remote transfer

A9L15585

⚠ Discontinued on: Jan 23, 2021 AD

⚠ Discontinued

### Main

Range of product	IPF
range of product	Acti9
Product name	Acti9 iPF
Product or component type	Surge arrester
Device short name	iPF65r
Device application	Distribution
Standards	EN 61643-11 IEC 61643-11
Product certifications	CE
Quality labels	KEMA-KEUR NF OVE
Poles description	4P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	TN-C

### Complementary

Surge arrester class type	Type 2
Surge arrester technology	MOV
[Ue] rated operational voltage	230/400 V AC (+/- 10 %) at 50/60 Hz
Nominal discharge current	Common mode: 20 kA (L/PE) Common mode: 20 kA (N/PE)
Maximum discharge current	Common mode: 65 kA L/PE Common mode: 65 kA N/PE
[Uc] maximum continuous operating voltage	Common mode: 340 V L/PE Common mode: 340 V N/PE
Maximum [Up] voltage protection level	Common mode <1.5 kV type 2 L/PE Common mode <1.5 kV type 2 N/PE
[I total] discharge current	260 kA
Disconnecter device type	Associated circuit breaker IC60N 50 A curve C - Icu 10 kA Associated circuit breaker IC60H 50 A curve C - Icu 15 kA Associated circuit breaker NG125N 50 A curve C - Icu 25 kA Associated circuit breaker NG125H 50 A curve C - Icu 36 kA Associated circuit breaker NG125L 50 A curve C - Icu 50 kA

<b>Signalling circuit voltage</b>	0.25 A/250 V AC 50/60 Hz
<b>Mounting mode</b>	Clip-on (DIN rail)
<b>9 mm pitches</b>	8
<b>Height</b>	81.4 mm
<b>Width</b>	72 mm
<b>Depth</b>	69 mm
<b>Colour</b>	White (RAL 9003)
<b>Connections - terminals</b>	Tunnel type terminal (downside) 2.5...35 mm <sup>2</sup> Tunnel type terminal (upside) 2.5...35 mm <sup>2</sup>
<b>Tightening torque</b>	2.5 N.m
<b>Compatibility code</b>	IPF65r
<b>Market segment</b>	Small commercial

## Environment

<b>IK degree of protection</b>	IK03 conforming to IEC 62262
<b>Relative humidity</b>	5...90 %
<b>Operating altitude</b>	2000 m
<b>Ambient air temperature for operation</b>	-25...60 °C
<b>Ambient air temperature for storage</b>	-40...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	7.5 cm
<b>Package 1 Width</b>	8 cm
<b>Package 1 Length</b>	8.7 cm
<b>Package 1 Weight</b>	0.508 kg



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

SCIP Number **Acfffb32-bc17-43e8-bdb6-e04a88d3170b**

EU RoHS Directive [Compliant By Exemption](#)

Halogen-free status **Halogen free plastic parts product**

### Use Longer




#### Lifetime extension

Repair **No**

### Use Again



#### Repack and remanufacture

WEEE Label  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**