

SIMATIC IPC277E (Nanopanel PC); 7" Touch TFT; 2x 10/100/1000 Mbps Ethernet RJ45; 1x display port graphic; 1x USB 3.0; 2x USB 2.0; 1x serial (COM 1); CFast slot; 24 V DC power supply Celeron N2807 (2C/2T) 4 GB RAM; WIN Embedded Standard 7E SP1, English; 64 bit 240 GB SSD without SIMATIC software

General information	
Product type designation	IPC277E
Display	
Design of display	7" TFT touch
Screen diagonal	7 in
Resolution (pixels)	
• Horizontal image resolution	800 pixel
• Vertical image resolution	480 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	80 000 h
Control elements	
Touch operation	
• Design as touch screen	Yes; analog, resistive
Installation type/mounting	
central design	Yes
Mounting in portrait format possible	Yes
Power loss	
In full configuration	26 W
Dimensions	
Width of the housing front	214 mm
Height of housing front	158 mm
Mounting cutout, width	197 mm
Mounting cutout, height	141 mm
mounting depth	77 mm
Weights	
Weight, approx.	1.5 kg
Classifications	

	Version	Classification
eClass	14	19-20-01-03
eClass	12	19-20-01-03
eClass	9.1	19-20-01-03
eClass	9	19-20-01-03
eClass	8	27-24-23-01
eClass	7.1	27-24-23-01
eClass	6	27-24-23-01
ETIM	10	EC001414
ETIM	9	EC001414
ETIM	8	EC001414
ETIM	7	EC001414

Approvals / Certificates		
General Product Approval	EMV	other



[Confirmation](#)

other	Environment
-------	-------------

[Confirmation](#)

[Environmental Con-
firmations](#)



last modified:

11/25/2025