

ETU VT250, 4-pole, line protection ETU DPN, LI IR=63...160A, overload protection IRM=4...8kA short-circuit protection, neutral conductor protection IRN=0.5 to 1xIR screw terminal connections in scope of delivery of switching unit



Model			
product brand name	SENTRON		
product designation	Electronic Trip Units (ETU)		
design of the product	ETU DPN, LI IR= 63 to 160 A		
Accessories			
accessories	Accessory for VT250		
Mechanical Design			
Net Weight	274 g		
Approvals Certificates			
Environment	General Product Approval	Test Certificates	other

[Environmental Conformations](#)



[Confirmation](#)



[Type Test Certificates/Test Report](#)

[Confirmation](#)

other



[Miscellaneous](#)

### Further information

- Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=3VT9216-6BC00>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/3VT9216-6BC00>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)  
[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mifb=3VT9216-6BC00](https://www.automation.siemens.com/bilddb/cax_en.aspx?mifb=3VT9216-6BC00)
- CAx-Online-Generator  
<https://www.siemens.com/cax>
- Tender specifications  
<https://www.siemens.com/specifications>
- Characteristic curves  
[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

---

last modified:

6/15/2025 

