


Product data sheet

Specifications



contactor coil, TeSys D LX1D, 208 V 60 Hz

LX1D8L6

ⓘ Discontinued

Main

Range	TeSys
Product or Component Type	Contactor coil
Range compatibility	TeSys TeSys D LC1D contactor
Control circuit type	AC
Coil type	AC 60 Hz
[Uc] control circuit voltage	208 V AC 60 Hz

Complementary

Control circuit voltage limits	0.85...1.1 Uc (at <131 °F (55 °C))
Average resistance	67.92 Ohm 68 °F (20 °C)
Inrush power in VA	300 VA 0.8 3P or 4P 68 °F (20 °C))
Hold-in power consumption in VA	22 VA 60 Hz 0.3 3P or 4P 68 °F (20 °C))
Mechanical durability	10000000 cycles
Connections - terminals	Control circuit connector 1 0.002...0.006 in² (1...4 mm²)flexible with cable end Control circuit connector 1 0.002...0.006 in² (1...4 mm²)flexible without cable end Control circuit connector 1 0.002...0.006 in² (1...4 mm²)solid without cable end Control circuit connector 2 0.002...0.004 in² (1...2.5 mm²)flexible with cable end Control circuit connector 2 0.002...0.006 in² (1...4 mm²)flexible without cable end
Tightening torque	Control circuit 10.6 lbf.in (1.2 N.m) connector
Net Weight	0.57 lb(US) (0.26 kg)

Environment

Ambient Air Temperature for Operation	68 °F (20 °C)
---------------------------------------	---------------

Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	3389110898323
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1
Package weight(Lbs)	10.05 oz (285 g)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.