

Product datasheet

Specifications



reversing contactor TeSys LC2-D - 3 poles - AC-3 440V 95 A - coil 115 V AC

LC2D95FE5

EAN Code: 3389110960709

! Discontinued

Main

| | |
|---------------------------|----------------------|
| Range of product | TeSys D |
| Product or component type | Reversing contactor |
| Device short name | LC2D |
| Contactor application | Motor control |
| Utilisation category | AC-4 AC-2 AC-3 |
| Control circuit type | AC |
| Coil type | Standard |
| Poles description | 3P |
| Pole contact composition | 3 NO |

Complementary

| | |
|-------------------------------|---|
| Assembly style | Ready assembled |
| Coil technology | Without built-in bidirectional peak limiting diode suppressor |
| Protective cover | With |
| Auxiliary contact composition | 1 NO + 1 NC |
| Interlocking type | Mechanical |
| Overvoltage category | III |
| Mounting support | Rail Plate |
| Associated fuse rating | 10 A gG for control circuit conforming to IEC 60947-5-1 |
| Mechanical durability | 10000000 cycles 4000000 cycles |
| Height | 140 mm |
| Width | 182 mm |
| Depth | 158 mm |
| Product weight | 3.2 kg |

Environment

| | |
|------------------|---|
| Standards | IEC 60947-5-1 IEC 60947-4-1 UL 508 EN 60947-4-1 EN 60947-5-1 CSA C22.2 No 14 |
|------------------|---|

| | |
|-------------------------------|--|
| Product certifications | CCC BV DNV GOST LROS (Lloyds register of shipping) RINA GL |
|-------------------------------|--|

| | |
|--|------------|
| Ambient air temperature for operation | -5...60 °C |
|--|------------|

| | |
|--|-------------|
| Ambient air temperature for storage | -60...80 °C |
|--|-------------|

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 18 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins