

Product datasheet

Specifications



DeviceNet communication card - 125 kbps

VW3A3E309

Main

Product or component type	Communication card
Range compatibility	Altivar 61 Plus Altivar 71 Plus
Communication port protocol	DeviceNet
Connector type	1 screw connector 5 contacts at intervals of 5.08
Transmission rate	500 kbps 125 kbps 250 kbps

Complementary

Number of addresses	1...63
Exchange mode	Outputs : polled Inputs : polled, change of state, cyclic
Communication service	I/O profile Communication monitoring can be inhibited, adjustable Allen-Bradley drive profile CiA 402 profile : "Device profile Drives and Motion Control" CIP AC Drive (02) profile
Display type	1 dual colour LED for MNS (status) Graphic display terminal for control word received Graphic display terminal for reference received
Net weight	0.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.2 cm
Package 1 Width	17.2 cm
Package 1 Length	23.5 cm
Package 1 Weight	297.0 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No