

# Product datasheet

Specifications



## voltage release Compact MX - 48 V DC

29392

⚠ Discontinued

### Main

Range	ComPact
Range of product	NR400...630 NS100...250 NB400...600 NR100...250 NS400...630 NS100...250 DC NSF150...250 NS400...630 DC NSJ400...600 NS125E
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Shunt trip release
[Uc] control circuit voltage	48 V DC
Range compatibility	ComPact ComPact NS ComPact Compact NB ComPact Compact NR ComPact Compact NSF ComPact Compact NSJ

### Complementary

Operating threshold	0.7...1.1 x Un
Control signal type	Maintained Impulse
Impulse duration	>= 20 ms
Auxiliary connection terminal	Screw terminal 0...1.5 mm <sup>2</sup>

### Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins