

# Product datasheet

Specifications



## Capacitor contactor, Tesys Deca, 16.7kVAR at 400/415V 50Hz, 440V AC 50/60Hz coil

LC1DGK11R7

! Discontinued

### Main

Range	TeSys
Product name	TeSys LC1D.K TeSys Deca
Product or component type	Capacitor duty contactor
Device short name	LC1DGK
Contactur application	Power factor correction
Poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit: $\leq 690$ V AC 50/60 Hz
Reactive power rating	16.7 kvar at 400...440 V AC 50/60 Hz 55 °C 24 kvar at 660...690 V AC 50/60 Hz 55 °C 8.5 kvar at 220...240 V AC 50/60 Hz 55 °C
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	440 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 1 NC
Mounting support	Plate Rail
Standards	VDE 0560 IEC 60070 IEC 60831 NF C 54-100
Product certifications	UL CSA
Connections - terminals	Power circuit: connector 1 4 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: connector 1 6 mm <sup>2</sup> - cable stiffness: solid with cable end Power circuit: connector 2 2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: connector 2 6 mm <sup>2</sup> - cable stiffness: solid with cable end
Tightening torque	Power circuit: 1.7 N.m - on connector

### Complementary

Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
-------------------------	--

### Environment

IP degree of protection	IP2X conforming to IEC 60529 IP2X conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068-2-30

---

<b>Ambient air temperature for operation</b>	-5...60 °C
<b>Ambient air temperature for storage</b>	-60...80 °C
<b>Operating altitude</b>	0...3000 m
<b>Height</b>	130 mm
<b>Width</b>	45 mm
<b>Depth</b>	122 mm
<b>Net weight</b>	0.45 kg

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1

---

## Contractual warranty

---

<b>Warranty (in months)</b>	18
-----------------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No