

Product data sheet

Specifications



Multi9 - C60 UL489 - MCB - 2P - 0.5 A - C Curve - 480Y/277 V - 10 kA - tunnel t

MGN61311

⚠ Discontinued on: May 31, 2021

⚠ End-of-service on: Jun 15, 2021

⚠ Discontinued

Main

Range	Multi9
Product name	Multi9 C60
Product or Component Type	Miniature circuit-breaker
Device short name	C60 UL489
Device Application	Distribution
Poles description	2P
Number of protected poles	2
Line Rated Current	0.5 A 77 °F (25 °C)
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	10 kA AIR 480Y/277 V AC UL 489 10 kA AIR 480Y/277 V AC CSA C22.2 No 5.2 10 kA Icu 480Y/277 V AC EN/IEC 60947-2 10 kA Icu 480Y/277 V AC GB 14048.2
Suitability for isolation	Yes EN/IEC 60947-2
Standards	GB 14048.2 EN/IEC 60947-2 UL 489 CSA C22.2 No 5
Product certifications	CSA CCC IEC UL

Complementary

Network Frequency	50/60 Hz
[Ue] rated operational voltage	480Y/277 V AC
Magnetic tripping limit	8.5 x In +/- 20 % AC
Limitation class	3 EN/IEC 60947-2
[Ui] rated insulation voltage	500 V AC EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kVEN/IEC 60947-2
Contact position indicator	Yes
Control Type	Toggle

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Local signalling	ON/OFF indication
Mounting Mode	Clip-on
Mounting Support	DIN rail
9 mm pitches	4
Height	5.6 in (141 mm)
Width	1.4 in (36 mm)
Depth	2.7 in (68.7 mm)
Net Weight	0.49 lb(US) (0.22 kg)
color	Gray
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminal top or bottom) - 1 0.002...0.002 in ² (1...1.5 mm ²) AWG 18...AWG 16) - rigid Tunnel type terminal top or bottom) - 2 0.002...0.002 in ² (1...1.5 mm ²) AWG 18...AWG 16) - rigid
Tightening torque	7.08 lbf.in (0.8 N.m) top or bottom

Environment

IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	3 EN/IEC 60947-2
Overvoltage category	IV
Tropicalisation	2 IEC 60068-1
Relative humidity	95 % 131 °F (55 °C)
Operating altitude	6561.68 ft (2000 m)
Ambient air temperature for operation	-22...158 °F (-30...70 °C)
Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)

Ordering and shipping details

Category	00915-C60N MINIATURE CIRCUIT BREAKER-UL489
Discount Schedule	DE2
GTIN	785901474609
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.5 in (3.9 cm)
Package 1 Width	3.0 in (7.6 cm)
Package 1 Length	5.6 in (14.3 cm)
Package weight(Lbs)	11.5 oz (326 g)

Contractual warranty

Warranty (in months)

18



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

[EU RoHS Directive](#)

Compliant

SCIP Number

40a4e715-7fff-45ff-88bf-38212f6a80a5

REACH Regulation

[REACH Declaration](#)

Halogen content performance

Halogen free product

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.