

Product datasheet

Specifications



earth-leakage module Vigi C60 - 2P - 25 A - 127..240 V - 10 mA - class AC

MGV250102

⚠ Discontinued on: 17 Nov 2017

⚠ Discontinued

Main

Range of product	C60
Device short name	Vigi C60
Poles description	2P
Neutral position	Left
[In] rated current	25 A
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	127...240 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage sensitivity	10 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Class AC
9 mm pitches	4

Complementary

Device location in system	Outgoer
Residual current tripping technology	Voltage dependent
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2
Mounting support	35 mm symmetrical DIN rail
Height	87 mm
Width	72 mm
Depth	74 mm
Net weight	0.12 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals0.5...16 mm² flexible Tunnel type terminals0.5...25 mm² rigid
Wire stripping length	14 mm

Environment

Standards	IEC 60947-2
Pollution degree	3 conforming to IEC 60947-2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Tropicalisation	2 conforming to IEC 60947-2
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...70 °C



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins