



SIMATIC ET 200BL, terminal block 24 V for I/O modules, spare part, 18x push-in terminals, packing unit: 5 units

General information			
Product type designation		Terminal block 24V	
Product function			
● I&M data		No	
Supply voltage			
external protection for power supply lines		Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic	
Current carrying capacity			
For P1 and P2 bus, max.		10 A	
For process terminals, max.		2 A; Point of contact, derating depends on the module	
Ambient conditions			
Ambient temperature during operation			
● horizontal installation, min.		-30 °C	
● horizontal installation, max.		60 °C	
● vertical installation, min.		-30 °C	
● vertical installation, max.		50 °C	
Altitude during operation relating to sea level			
● Installation altitude above sea level, max.		5 000 m; Restrictions for installation altitudes > 2 000 m, see manual	
Accessories			
Color coding labels			
● for process terminals		CC00 to CC09	
Connection method			
Terminals			
● Terminal type		Push-in terminal	
● Conductor cross-section, min.		0.14 mm²; follow detailed information in System manual of ET 200BL	
● Conductor cross-section, max.		2.5 mm²; follow detailed information in System manual of ET 200BL	
● Number of process terminals to I/O module		16	
● Number of terminals with connection to P1 and P2 bus		2	
Dimensions			
Width		15 mm	
Height		65 mm	
Depth		29 mm	
Weights			
Weight, approx.		17 g	
Classifications			
		Version	Classification
		eClass	14
		eClass	12
			27-24-26-92
			27-24-26-92

eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)

last modified: 9/19/2025 