

Product data sheet

Specifications



SH3 servomotor, 70mm, 3 stacks, high Torque, keyed Shaft, SinCos Multiturn 128, Brake, angular, IP54/65

SH30703M12F2000

! Discontinued

! Discontinued on: Jul 23, 2025

! End-of-service on: Dec 31, 2025

Main

Range compatibility	PacDrive 3
Device short name	SH3
Product or component type	Servo motor

Complementary

Maximum mechanical speed	8000 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	2.1 A
Continuous stall torque	26.02 lbf.in (2.94 N.m) 115...480 V three phase
Continuous power	830 W
Peak stall torque	100.01 lbf.in (11.3 N.m) 115...480 V three phase
Nominal output power	240 W 115 V single phase 460 W 230 V single phase 880 W 400 V three phase 1030 W 480 V three phase
Nominal torque	26.99 lbf.in (3.05 N.m) 115 V single phase 26.11 lbf.in (2.95 N.m) 230 V single phase 23.28 lbf.in (2.63 N.m) 400 V three phase 23.28 lbf.in (2.63 N.m) 480 V three phase
Nominal speed	750 rpm 115 V single phase 1500 rpm 230 V single phase 3000 rpm 400 V three phase 3600 rpm 480 V three phase
Maximum current Irms	8.7 A
Shaft end	Parallel key
Shaft diameter	0.6 in (14 mm)
Shaft length	1.2 in (30 mm)
Key width	0.2 in (5 mm)
IP degree of protection	IP54 shaft bushing without shaft seal ring: conforming to IEC 60034-5 IP65 motor: conforming to IEC 60034-5 IP65 shaft bushing: conforming to IEC 60034-5
Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	128 periods

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Holding brake	With
Holding torque	26.6 lbf.in (3 N.m)
Mounting support	International standard flange
Motor flange size	2.8 in (70 mm)
Electrical connection	Straight connector
Torque constant	1.4 N.m/A 248 °F (120 °C)
Back emf constant	95 V/krpm 68 °F (20 °C)
Number of motor poles	3
Rotor inertia	0.807 kg.cm ²
Stator resistance	10.7 Ohm
Stator inductance	76.85 mH
Maximum radial force Fr	730 N 1000 rpm 580 N 2000 rpm 510 N 3000 rpm 460 N 4000 rpm 430 N 5000 rpm 400 N 6000 rpm
Maximum axial force Fa	80 N
Type of cooling	Natural convection
Length	10 in (254 mm)
Centring collar diameter	2.4 in (60 mm)
Centring collar depth	0.10 in (2.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.2 in (5.5 mm)
Circle diameter of the mounting holes	3.2 in (82 mm)
Net weight	8.4 lb(US) (3.8 kg)
Sizing reference	SH30703M
Network number of phases	3
Temperature copper hot	266 °F (130 °C)
Electrical connection	rotatable right angled connector

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No