


Product datasheet

Specifications



contactor coil - FF - 30 V DC

LX4FF030

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range	TeSys
Product or component type	Contacteur coil
Device short name	LX4FF
Range compatibility	TeSys TeSys F LC1F contacteur
Product compatibility	LC1F150 LC1F115
Control circuit type	DC low consumption
[Uc] control circuit voltage	30 V DC
Average resistance	1.78 Ohm inrush at 20 °C 296.7 Ohm holding at 20 °C
Operating time	30...40 ms closing 30...50 ms opening

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational: 0.85...1.1 Uc (at 55 °C) Drop-out: 0.15...0.2 Uc (at 55 °C)

Environment

Ambient air temperature for operation	-5...55 °C
---------------------------------------	------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **Yes**

Use Longer



Lifetime extension

Repair **No**