

Product datasheet

Specifications



voltage release Compact MX - 30 V DC

29391

⚠ Discontinued

Main

Range	ComPact
Range of product	NR400...630 NS125E NS400...630 NB400...600 NSF150...250 NS100...250 DC NS400...630 DC NS100...250 NR100...250 NSJ400...600
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Shunt trip release
[Uc] control circuit voltage	30 V DC
Range compatibility	ComPact ComPact NS ComPact Compact NB ComPact Compact NR ComPact Compact NSF ComPact Compact NSJ

Complementary

Operating threshold	0.7...1.1 x Un
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Auxiliary connection terminal	Screw terminal 0...1.5 mm ²

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins