



Product availability: Stock - Normally stocked in distribution facility

Price*: 4280.00 USD



Main

Commercial Status	Commercialised
Range of product	Modicon Quantum automation platform
Product or component type	Analogue output module

Complementary

Analogue output number	8
Addressing requirement	8 output words
Loop voltage	6...30 V DC
Voltage drop	6...30 V 25 mA
Analogue output range	4...20 mA 0...4095 counts 4...20 mA 0...16000 counts 0...25 mA 0...25000 counts 0...20 mA 0...20000 counts
Absolute accuracy error	+/- 0.2 % of full scale at 77 °F (25 °C)
Linearity	+/- 4 µA 4...20 mA 0...16000 counts +/- 4 µA 0...25 mA 0...25000 counts +/- 4 µA 0...20 mA 0...20000 counts +/- 12 µA 4...20 mA 0...4095 counts
Accuracy drift according to temperature	0.007 % of full scale/°C maximum 0.004 % of full scale/°C typical
Isolation between channels and bus	1780 V for 1 minute AC
Update time	5 ms
Setting time	1.6 ms to 5% of the final value 3.2 ms to +/-0.1% of the final value
Fault type	Open circuit 4...20 mA
Bus current requirement	550 mA
Power dissipation in W	5 W
External power requirement	6...30 V
Marking	CE
Local signalling	8 LEDs red channel fault 8 LEDs green channel is turned on 1 LED red external fault 1 LED green bus communication is present (Active)
Module format	Standard
Product weight	0.66 lb(US) (0.3 kg)

Environment

Product certifications	CUL FM Class 1 Division 2
Standards	CSA C22.2 No 142 UL 508
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) 80...2000 MHz conforming to IEC 801-3
Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % without condensation
Operating altitude	<= 16404.2 ft (5000 m)

Ordering and shipping details

Category	18155 - QUANTUM I/O & POWER SUPPLIES
Discount Schedule	PC21
GTIN	00785901327004
Nbr. of units in pkg.	1
Package weight(Lbs)	1.04
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0846 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental Profile
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------