


Product data sheet

Specifications



servo motor MH3 140 19,5Nm,no
key,multi,brake,IP65/IP67,3kRPM

MH31402P02F2200

⚠ Discontinued on: Oct 9, 2023

⚠ Discontinued

Main

Range compatibility	PacDrive 3
Device short name	MH3
Product or component type	Servo motor

Complementary

Maximum mechanical speed	4000 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	16.83 A
Continuous stall torque	163.7 lbf.in (18.5 N.m), 115...480 V, three phase
Continuous power	3730 W
Peak stall torque	491.2 lbf.in (55.5 N.m), 115...480 V, three phase
Nominal output power	1.71 W, 115 V 2.93 W, 230 V 3.73 W, 400 V 3.73 W, 480 V
Nominal torque	144.62 lbf.in (16.34 N.m) LXM52 14.87 mA, 115 V, three phase 123.9 lbf.in (14.0 N.m) LXM52 13.13 mA, 230 V, single phase 90.01 lbf.in (10.17 N.m) LXM52 9.76 mA, 400 V, three phase 90.01 lbf.in (10.17 N.m) LXM52 9.76 mA, 480 V, three phase 144.62 lbf.in (16.34 N.m) LXM62 14.87 mA, 115 V, single phase 123.9 lbf.in (14.0 N.m) LXM62 13.13 mA, 230 V, single phase 90.01 lbf.in (10.17 N.m) LXM62 9.76 mA, 400 V, three phase 90.01 lbf.in (10.17 N.m) LXM62 9.76 mA, 480 V, three phase
Nominal speed	1000 rpm LXM52 14.87 mA, 115 V, single phase 2000 rpm LXM52 13.13 mA, 230 V, single phase 3500 rpm LXM52 9.76 mA, 400 V, three phase 3500 rpm LXM52 9.76 mA, 480 V, three phase 1000 rpm LXM62 14.87 mA, 115 V, single phase 2000 rpm LXM62 13.13 mA, 230 V, single phase 3500 rpm LXM62 9.76 mA, 400 V, three phase 3500 rpm LXM62 9.76 mA, 480 V, three phase
Maximum current Irms	57.42 A
Shaft end	Smooth shaft
Second shaft	Without second shaft end
Shaft diameter	0.9 in (24 mm)
Shaft length	2.0 in (50 mm)
IP degree of protection	IP65 standard
Encoder type	Multiturn SinCos Hiperface

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Speed feedback resolution	128 periods
Holding brake	With
Holding torque	159.3 lbf.in (18 N.m)
Mounting support	International standard flange
Motor flange size	5.5 in (140 mm)
Electrical connection	Rotatable right-angled connectors
Torque constant	1.1 N.m/A 248 °F (120 °C)
Back emf constant	70.7 V/krpm
Number of motor poles	10
Rotor inertia	33.5 kg.cm²
Stator resistance	0.23 Ohm
Stator inductance	2.99 mH
Stator electrical time constant	13 ms
Maximum radial force Fr	2240 N 1000 rpm 1780 N 2000 rpm 1550 N 3000 rpm
Brake pull-in power	18 W
Type of cooling	Natural convection
Length	8.9 in (227 mm)
Centring collar diameter	5.1 in (130 mm)
Centring collar depth	0.1 in (3.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.4 in (11 mm)
Circle diameter of the mounting holes	6.5 in (165 mm)
Net weight	31.5 lb(US) (14.3 kg)
Sizing reference	MH31402P
Temperature copper hot	275 °F (135 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.2 in (26.0 cm)
Package 1 Width	7.9 in (20.0 cm)
Package 1 Length	23.2 in (59.0 cm)
Package 1 Weight	29.3 lb(US) (13.3 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	Nej