

Product datasheet

Specifications

Output shorting link, GoPact MTS 630, 400-630A



GMSCONOSL04630

Main

Range of product	GoPact MTS
Product or component type	Shorting link
Device application	Connection
Range compatibility	GoPact MTS 630
[In] rated current	400...630 A
Frame size	4
Quantity per set	4 pieces

Complementary

Connections - terminals	Bolted connection
-------------------------	-------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11 cm
Package 1 Width	5.7 cm
Package 1 Length	10 cm
Package 1 Weight	0.686 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Packaging

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Take-back	No
-----------	----

Technical Illustration

Assembly's dimensions

