


Product datasheet

Specifications



UNIVERSAL POWER SUPPLY BLOCK 400-630A

04074

⚠ Discontinued on: 23 Sept 2025

⚠ Discontinued

Main

Range	Linergy
Range of product	Linergy
Product or component type	Universal power supply block
Product name	Linergy BW
product name	Prisma Prisma P enclosure Prisma Prisma G enclosure Linergy Linergy BW busbar
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Product certifications	ASEFA

Complementary

Cubicle-device connection	Linergy BW busbar
Poles description	3P 4P
installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Installed device	<p>ComPact: fixed NSX400 without earth leakage protection - control: toggle vertical installation</p> <p>ComPact: fixed NSX400 without earth leakage protection - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed NSX400 with earth leakage protection - control: toggle vertical installation</p> <p>EasyPact: fixed CVS400 without earth leakage protection - control: toggle vertical installation</p> <p>EasyPact: fixed CVS630 without earth leakage protection - control: toggle vertical installation</p> <p>EasyPact: fixed CVS400 without earth leakage protection - control: direct front rotary handle vertical installation</p> <p>EasyPact: fixed CVS630 without earth leakage protection - control: direct front rotary handle vertical installation</p> <p>EasyPact: fixed CVS400 with earth leakage protection - control: toggle vertical installation</p> <p>EasyPact: fixed CVS630 with earth leakage protection - control: toggle vertical installation</p> <p>ComPact: fixed NSX630 without earth leakage protection - control: toggle vertical installation</p> <p>ComPact: fixed NSX630 without earth leakage protection - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed NSX630 with earth leakage protection - control: toggle vertical installation</p> <p>ComPact: fixed NSX400 with earth leakage protection - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed NSX630 with earth leakage protection - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed INS320...400 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed INS500...630 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed INV320...400 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed INV500...630 - control: direct front rotary handle vertical installation</p> <p>EasyPact: fixed CVS400 with earth leakage protection - control: direct front rotary handle vertical installation</p> <p>EasyPact: fixed CVS630 with earth leakage protection - control: direct front rotary handle vertical installation</p>
[Ie] rated operational current	630 A
[In] rated current	630 A
Net weight	1 kg
Quantity per set	Set of 2

rotary handle vertical 4P 1 direct with long terminal shield 18
600 mm Prisma G floor-standing enclosure EasyPact CVS630 with fixed toggle
vertical 3P 1 direct with long terminal shield 15
600 mm Prisma G wall-mounted enclosure EasyPact CVS630 with fixed toggle
vertical 3P 1 direct with long terminal shield 15
600 mm Prisma G floor-standing enclosure EasyPact CVS630 with fixed toggle
vertical 4P 1 direct with long terminal shield 15
600 mm Prisma G wall-mounted enclosure EasyPact CVS630 with fixed toggle
vertical 4P 1 direct with long terminal shield 15
600 mm Prisma G floor-standing enclosure EasyPact CVS630 with fixed direct front
rotary handle vertical 3P 1 direct with long terminal shield 18
600 mm Prisma G wall-mounted enclosure EasyPact CVS630 with fixed direct front
rotary handle vertical 3P 1 direct with long terminal shield 18
600 mm Prisma G floor-standing enclosure EasyPact CVS630 with fixed direct front
rotary handle vertical 4P 1 direct with long terminal shield 18
600 mm Prisma G wall-mounted enclosure EasyPact CVS630 with fixed direct front
rotary handle vertical 4P 1 direct with long terminal shield 18
600 mm Prisma G floor-standing enclosure ComPact NSX400 with fixed toggle
vertical 3P 1 direct with long terminal shield 14
600 mm Prisma G wall-mounted enclosure ComPact NSX400 with fixed toggle
vertical 3P 1 direct with long terminal shield 14
600 mm Prisma G floor-standing enclosure ComPact NSX400 with fixed toggle
vertical 4P 1 direct with long terminal shield 14
600 mm Prisma G wall-mounted enclosure ComPact NSX400 with fixed toggle
vertical 4P 1 direct with long terminal shield 14
600 mm Prisma G floor-standing enclosure ComPact NSX400 with fixed direct front
rotary handle vertical 3P 1 direct with long terminal shield 18
600 mm Prisma G wall-mounted enclosure ComPact NSX400 with fixed direct front
rotary handle vertical 3P 1 direct with long terminal shield 18
600 mm Prisma G floor-standing enclosure ComPact NSX400 with fixed direct front
rotary handle vertical 4P 1 direct with long terminal shield 18
600 mm Prisma G wall-mounted enclosure ComPact NSX400 with fixed direct front
rotary handle vertical 4P 1 direct with long terminal shield 18
600 mm Prisma G floor-standing enclosure ComPact NSX630 with fixed toggle
vertical 3P 1 direct with long terminal shield 15
600 mm Prisma G wall-mounted enclosure ComPact NSX630 with fixed toggle
vertical 3P 1 direct with long terminal shield 15
600 mm Prisma G floor-standing enclosure ComPact NSX630 with fixed toggle
vertical 4P 1 direct with long terminal shield 15
600 mm Prisma G wall-mounted enclosure ComPact NSX630 with fixed toggle
vertical 4P 1 direct with long terminal shield 15
600 mm Prisma G floor-standing enclosure ComPact NSX630 with fixed direct front
rotary handle vertical 3P 1 direct with long terminal shield 18
600 mm Prisma G wall-mounted enclosure ComPact NSX630 with fixed direct front
rotary handle vertical 3P 1 direct with long terminal shield 18
600 mm Prisma G floor-standing enclosure ComPact NSX630 with fixed direct front
rotary handle vertical 4P 1 direct with long terminal shield 18
600 mm Prisma G wall-mounted enclosure ComPact NSX630 with fixed direct front
rotary handle vertical 4P 1 direct with long terminal shield 18

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.5 cm
Package 1 Width	19.5 cm
Package 1 Length	24 cm
Package 1 Weight	955 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Packaging

EU RoHS Directive	Compliant
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer

Lifetime extension

Repair	No
--------	----

Use Again

Repack and remanufacture

Take-back	No
-----------	----

Image of product / Alternate images

Alternative

