


Data sheet for dv/dt filter plus VPL

Article No. : 6SL3000-2DH31-5AA0



Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
------------	--

Output current	150 A
----------------	-------

General technical specifications		
----------------------------------	--	--

Power loss	dv/dt reactor	Voltage Peak Limiter (VPL)
at 690 V / 50 Hz	0.389 kW	0.020 kW
at 575 V / 60 Hz	0.408 kW	0.019 kW
at 690 V / 150 Hz	0.436 kW	0.018 kW

Connections	
-------------	--

Cable length	
--------------	--

for motor, max. (shielded)	300 m (984 ft)
for motor, max. (unshielded)	450 m (1,476 ft)

Design	dv/dt reactor	Voltage Peak Limiter (VPL)
Power cable	1 x hole for M10	-
Load	1 x hole for M10	-
PE conductor	M6 screw	M8 stud
dv/dt reactor	-	M8 nut
DC link	-	M8 nut

Mechanical data		
-----------------	--	--

Degree of protection	IP00	
----------------------	------	--

	dv/dt reactor	Voltage Peak Limiter (VPL)
Net weight	50 kg (110 lb)	6 kg (13 lb)

Dimensions		
------------	--	--

Width	350 mm (13.80 in)	263 mm (10.40 in)
Height	320 mm (12.60 in)	265 mm (10.40 in)
Depth	227 mm (8.94 in)	188 mm (7.40 in)

Standards	
-----------	--

Compliance with standards	CE, cURus
---------------------------	-----------