

Product data sheet

Specifications



Circuit breaker frame, MasterPact MTZ2 10L1 drawout for MicroLogic X, 1000A, 150kA/415VAC (Icu), 4P

LV848254

Main

Range	MasterPacT
Product name	MasterPact MTZ2
Device short name	MTZ2 10 L1
Product or Component Type	Circuit breaker
Device Application	Power distribution protection
Poles description	4P
Neutral position	Left
Control unit	Without control unit
Product compatibility	control unit MicroLogic 2.0 X control unit MicroLogic 5.0 X control unit MicroLogic 6.0 X control unit MicroLogic 7.0 X control unit MicroLogic 2.0 Xi control unit MicroLogic 5.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 7.0 Xi
Line Rated Current	1000 A 104 °F (40 °C)
Performance type	L1 150 kA 415 V AC
[Ue] rated operational voltage	690 V AC 50/60 Hz
Suitability for isolation	Yes EN/IEC 60947-2
Selectivity category	Category B
Control Type	Push-button
Mounting Mode	Drawout

Complementary

[Icu] rated ultimate short-circuit breaking capacity	150 kA 220/415 V AC 50/60 Hz 150 kA 440 V AC 50/60 Hz 130 kA 500/525 V AC 50/60 Hz 100 kA 660/690 V AC 50/60 Hz
[Ics] rated service breaking capacity	150 kA 220/415 V AC 50/60 Hz 150 kA 440 V AC 50/60 Hz 130 kA 500/525 V AC 50/60 Hz 100 kA 660/690 V AC 50/60 Hz
[Icw] rated short-time withstand current	30 kA 0.5 s 30 kA 1 s 30 kA 3 s
[Icm] rated short-circuit making capacity	330 kA 220/415 V AC 50/60 Hz 330 kA 440 V AC 50/60 Hz 286 kA 500/525 V AC 50/60 Hz 220 kA 660/690 V AC 50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Integrated instantaneous protection (DIN in kA peak)	72...88 kA
Sensor rating	400 A 630 A 800 A 1000 A
[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
Power dissipation in W	150 W
Maximum breaking time	10 ms
Maximum closing response time	70 ms
Mounting Support	Rails Base plate
Upside connection	Front Rear
Downside connection	Front Rear
Connection pitch	4.5 in (115 mm)
Mechanical durability	25000 cycles with periodic preventive maintenance
Electrical durability	3000 cycles 690 V AC 50/60 Hz EN/IEC 60947-2 3000 cycles 440 V AC 50/60 Hz EN/IEC 60947-2
Height	Drawout circuit breaker with chassis: 17.3 in (439 mm) Drawout circuit breaker without chassis: 11.8 in (300 mm)
Width	Drawout circuit breaker with chassis: 21.9 in (556 mm) Drawout circuit breaker without chassis: 19.4 in (493 mm)
Depth	Drawout circuit breaker with chassis: 15.9 in (403 mm) Drawout circuit breaker without chassis: 11.8 in (300 mm)
Net Weight	264.6 lb(US) (120 kg)
Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-2 Annex H IEC 61557-12
Product Certifications	CE IECEE CB Scheme

Environment

IP degree of protection	IP30 conforming to EN 60529
Pollution degree	3 IEC 60947-1
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Operating altitude	0...6561.68 ft (0...2000 m) without derating 2000...5000 m with derating

Ordering and shipping details

GTIN	3606480806964
------	---------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Package 1 Height	13.0 in (33.0 cm)
Package 1 Width	20.5 in (52.0 cm)
Package 1 Length	11.8 in (30.0 cm)
Package weight(Lbs)	112.837 lb(US) (51.182 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	1 729 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	629 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	14 kg CO2 eq.
Carbon footprint of the installation phase [A5]	16 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	865 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	206 kg CO2 eq.

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
EU RoHS Directive	Compliant with Exemptions
SCIP Number	F31d8a4d-e9cb-4afc-bf2c-5965742ce772
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes
Silicon free	No

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Recyclability potential, in %	71
Circularity Profile	End of Life Information

Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.