



Product availability: Stock - Normally stocked in distribution facility

Price*: 2846.00 USD



Main

Commercial Status	Commercialised
Range of product	Modicon Quantum automation platform
Product or component type	Analogue output module

Complementary

Analogue output number	4
Addressing requirement	4 output words
Analogue output range	0...5 V $\geq$ 500 Ohm unipolar voltage 0...10 V $\geq$ 1000 Ohm unipolar voltage +/- 5 V $\geq$ 500 Ohm bipolar voltage +/- 10 V $\geq$ 1000 Ohm bipolar voltage
Analogue output resolution	12 bits
Analogue output current	-10...10 mA
Source resistance	0.1 Ohm
Cable length	$\leq$ 1312.34 ft (400 m)
Absolute accuracy error	+/- 0.15 % of full scale at 77 °F (25 °C)
Linearity	+/- 1 LSB
Accuracy drift according to temperature	0.007 % of full scale/°C maximum bipolar 0.005 % of full scale/°C maximum unipolar 0.004 % of full scale/°C bipolar 0.003 % of full scale/°C unipolar
Isolation between channels	500 V for 1 minute 47...63 Hz AC
Isolation between channels and bus	780 V for 1 minute AC
Update time	3 ms
Setting time	700 μ s to +/- 0.1 % of the final value maximum
Bus current requirement	700 mA
Power dissipation in W	$\leq$ 4.5 W
Associated fuse rating	0.063 mA 3 AG fast blow 250 V
Marking	CE
Local signalling	4 LEDs red channel fault 4 LEDs green channel is turned on 1 LED red external fault 1 LED green bus communication is present (Active)
Module format	Standard
Product weight	0.66 lb(US) (0.3 kg)

Environment

Product certifications	CUL FM Class 1 Division 2
Standards	CSA C22.2 No 142 UL 508
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) 80...2000 MHz conforming to IEC 801-3
Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % without condensation
Operating altitude	<= 16404.2 ft (5000 m)

Ordering and shipping details

Category	18155 - QUANTUM I/O & POWER SUPPLIES
Discount Schedule	PC21
GTIN	00785901792284
Nbr. of units in pkg.	1
Package weight(Lbs)	1.04
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1012 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental Profile
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------