



Main

Range of product	Multi9
Product or Component Type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[Uc] control circuit voltage	12...24 V AC 50/60 Hz 12...24 V DC
9 mm pitches	2

Complementary

Range compatibility	Multi9 Multi9 C60 Multi9 Multi9 ID Multi9 Multi9 N40
Local signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	35 mm symmetrical DIN rail
Height	3.2 in (82.5 mm)
Width	0.7 in (18 mm)
Depth	2.7 in (68 mm)
Connections - terminals	Clamp terminal - 1 0.004 in ² (2.5 mm ²) - flexible
Wire stripping length	0.4 in (9 mm)
Tightening torque	8.9 lbf.in (1 N.m)

Environment

Standards	EN/IEC 60947-5-1
Product Certifications	KEMA[RETURN]LCIE[RETURN]ASTA[RETURN]ASEFA
Tropicalisation	2 EN/IEC 60947-5-1
Relative humidity	95 % 131 °F (55 °C)
Ambient Air Temperature for Operation	-13...122 °F (-25...50 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	01078-DE2 MISC
Discount Schedule	DE2
GTIN	3303430269489
Returnability	No
Country of origin	BE

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------