

Product data sheet

Specifications



ASCO 6111 Load Bank

ASCOLBLV6111

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Max Capacity Rating 1050 kvar

Capacitance Rating 0.8 pF

Load Step Resolution 1 kvar

Voltage Rating 380...690 V AC 50/60 Hz

Inductor Load Tolerance 3 %

Provided Equipment
1 gland plate inside the enclosure
HRC fuse inside the enclosure
Voltage transformer 1 inside the enclosure
Cooling fans inside the enclosure

Connection Terminals Terminals neutral)

IP Protection
IP2X
IP54

Enclosure Material
Zintec
Aluminium
Steel

Color Gray RAL 7042)

Length 91.3 in (2320 mm)

Width 60.6 in (1540 mm)

Height 75.2 in (1910 mm)

Product Weight 7716.2 lb(US) (3500 kg)

Environmental

Standards
ISO 9001
CE
IEC 60309-2

Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer

Lifetime extension

Repair **No**