

Product data sheet

Specifications

SQUARE D



Discontinued

KA, KC, KH, KI MOULDED CASE CIRCUIT BREAKERs MECHANICAL LUG KIT (3)

CU250KA

Main

Circuit breaker type	KA/KH/KC/KI
----------------------	-------------

Complementary

Tightening torque	79.7 lbf.in (9 N.m) (AWG 4...250 kcmil) 247.8 lbf.in (28 N.m) 0.04...0.2 in² (25...120 mm²)
-------------------	--

Ordering and shipping details

Category	01078-DE2 MISC
Discount Schedule	DE2
GTIN	00785901068815
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package weight(Lbs)	16.000 oz (453.592 g)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

[EU RoHS Directive](#)

Compliant

California proposition 65

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Halogen content performance

Halogen free plastic parts product

PVC free

Yes

Use Longer



Lifetime extension

Repair

No