

Product datasheet

Specifications



ECOFIT Sepam S20/S40 with
Easergy P3U30, Russian, RS485,
155 V DC, 220...230 V AC/DC,
48...230 V

REL52436

! Discontinued

! Discontinued on: 09 Dec 2024

Main

Range of product	Easergy P3
User language	Russian

Complementary

Range compatibility	Sepam series 20 Sepam series 40
Input type	3 CT + I0
Physical interface	RS485
Switching voltage	155 V DC
[Ue] rated operational voltage	220...230 V AC/DC
[Us] rated supply voltage	48...230 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	30.0 cm
Package 1 Length	40.0 cm
Package 1 Weight	3.5 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No