

Product datasheet

Specifications



individual enclosure, Compact
INS250-100 to INS250, extended
red rotary handle on yellow front,
steel, IP55

31211

⚠ Discontinued on: 20 Jun 2023

⚠ Discontinued

Main

Range of product	INS250
Range	ComPact
Product or component type	Enclosure
Accessory / separate part category	Enclosure accessory
Range compatibility	ComPact ComPacT INS circuit breaker
enclosure type	Individual enclosure
Accessories included with enclosure	Red and yellow rotary handle
Enclosure material	Steel

Complementary

Enclosure mounting	Surface
compatible devices	INS250-160 INS250-100 INS250-200 INS250
Control type	Extended rotary handle
Type of front cover	Opaque
Width	350 mm
Height	450 mm
Depth	250 mm

Environment

IP degree of protection	IP55
IK degree of protection	IK08

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.0 cm
Package 1 Width	37.0 cm
Package 1 Length	84.0 cm
Package 1 Weight	15.778 kg

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

Contractual warranty

Warranty (in months)

18



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins