



Figure similar

spare part SIMATIC S7-300, connection IM 360 in central rack for connection of max. 3 expansion racks, with C-bus

Input current	
from backplane bus 5 V DC, max.	350 mA
Power loss	
Power loss, typ.	2 W
Hardware configuration	
Number of interfaces per CPU, max.	1
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	225 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	

[Manufacturer Declaration](#)



General Product Approval	EMV	For use in hazardous locations			
--------------------------	-----	--------------------------------	--	--	--

[Manufacturer Declaration](#)



[FM](#)



For use in hazardous locations			Maritime application		
--------------------------------	--	--	----------------------	--	--



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application					
----------------------	--	--	--	--	--



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025