


Product datasheet

Specifications



time delay relay for voltage release MN - 48V AC 50HZ - for NS80..NS630

29426

⚠ Discontinued on: 31 Mar 2021

⚠ Discontinued

Main

Device short name	MN delay unit
Product or component type	Time delay auxiliary
Device application	Control
Range compatibility	ComPact ComPact NS
[Uc] control circuit voltage	48 V AC 50/60 Hz 48 V DC

Complementary

Impulse duration	200 ms
Threshold tripping voltage	0.35...0.7 Un open 0.85 Un close
Supply holding power	4.5 VA
Supply inrush power	200 VA
Mounting mode	Fixed
Response time	< 50 ms

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins