


Product datasheet

Specifications



SDE fault trip indication contact, MasterPact NT, 1 changeover contact, standard 6A/240VAC, spare part

47078

Main

Device short name	SDE
Product or component type	Auxiliary contact
Device application	Connection
Range compatibility	Masterpact MasterPact NT circuit breaker
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	AC-12: 3 A at 690 V AC 50/60 Hz DC-12: 3 A at 24/48 V DC AC-12: 5 A at 240/380 V AC 50/60 Hz AC-12: 5 A at 480 V AC 50/60 Hz DC-12: 0.15 A at 250 V DC DC-12: 0.3 A at 125 V DC
Minimum load	100 mA at 24 V
Accessory / separate part category	Spare parts for MasterPact NT

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	5.0 cm
Package 1 Length	21.0 cm
Package 1 Weight	22.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.587 kg

Logistical informations

Country of origin	TH
-------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins