



insta contactor 0/1-automatic with 4 NO contact for 230 V AC, 400 V 25 A control  
230 V AC 220 V DC

Figure similar

| Model   |   |
|---|---|
| product brand name  | SENTRON   |
| product designation   | Installation contactor  |
| design of the product   | 4 NO contacts   |
| General technical data  |   |
| relative ON period of magnet coil   | 100 %   |
| type of voltage of the operating voltage  | AC  |
| type of voltage of the operating voltage for actuation                              | AC/DC   |
| Supply voltage  |   |
| operating voltage rated value   |   |
| • minimum   | 400 V   |
| • maximum   | 400 V   |
| Protection class  |   |
| protection class IP   | IP20  |
| Dissipation   |   |
| power loss [W] for rated value of the current at AC in hot operating state per pole | 2.2 W   |
| Control current   |   |
| control supply voltage  |   |
| • rated value   | 230 V   |
| • rated value maximum   | 230 V   |
| • at DC rated value   | 220 V   |
| Product details   |   |
| product component slide for manual operation  | Yes   |
| number of NC contacts   | 0   |
| number of NO contacts   | 4   |
| product extension installable supplementary devices                                 | Yes   |
| Connections   |   |
| installation or assembly note   | provision must be made for spacers to ensure heat dissipation |
| Mechanical Design   |   |
| height  | 90 mm   |
| width   | 35 mm   |
| depth   | 71 mm   |
| installation depth  | 70 mm   |
| number of modular width units   | 2   |
| Net Weight  | 280 g   |
| Approvals Certificates  |   |
| Environment   | General Product Approval                                      |



General Product Approval

Test Certificates

other

[Confirmation](#)



[Special Test Certificate](#)

[Confirmation](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT5030-6>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT5030-6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TT5030-6](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT5030-6)

CAX-Online-Generator


<https://www.siemens.com/cax>


Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)





last modified:

8/13/2025

