


Product data sheet

Specifications



Voltage release, TeSys GV5 GV6 GV7, MX shunt trip, 48V AC 50/60Hz

GV7AS055

⚠ Discontinued on: Jan 23, 2021

⚠ Discontinued

Main

Range	TeSys
Product or component type	Shunt trip
Device short name	GV7AS
Device application	Control
Range compatibility	TeSys TeSys GV5 TeSys TeSys GV6 TeSys TeSys GV7

Complementary

[Uc] control circuit voltage	48 V AC 50/60 Hz
Control circuit voltage limits	0.7...1.1 Un
[Ui] rated insulation voltage	690 V AC conforming to IEC 60947-1 600 V AC conforming to UL 508 600 V AC conforming to CSA C22.2 No 14
Threshold tripping voltage	0.2...0.75 Ue
Inrush power in VA	10 VA AC
Hold-in power consumption in VA	5 VA AC
Operating time	< 50 ms conforming to IEC 60947-1
On-load factor	100 %
Connections - terminals	Screw clamp terminals 1 cable(s) 1 mm ² flexible with cable end Screw clamp terminals 1 cable(s) 1.5 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 1.5 mm ² solid
Tightening torque	1.2 N.m on screw clamp terminals
Net weight	0.11 kg
Quantity per set	Set of 10

Contractual warranty

Warranty (in months)	18
----------------------	----

List Price displayed is VAT EXCLUSIVE.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins