

# Product data sheet

Specifications



## TeSys Deca - auxiliary contact block - 2 NO -

GK2AX22

⚠ Discontinued on: Jul 12, 2021

⚠ Discontinued

### Main

Range	TeSys
Device short name	GK2AX
Product or Component Type	Fault signalling contact
Product Compatibility	GK3EF
Mounting Location	Left side
Auxiliary contacts operation	Fault signal 2 NO
Pole contact composition	2 NO
Quantity per Set	Set of 10

### Complementary

[Ui] rated insulation voltage	500 V IEC 60947-1
[Ue] rated operational voltage	500 V
[Ith] conventional free air thermal current	6 A
Protection type	GB2CB... circuit breaker GG fuse 6 A
Rated operational power in VA	360 VA 48 V AC-15 20000 cycles 6 A 500 VA 110...127 V AC-15 20000 cycles 4.5 A 800 VA 220...240 V AC-15 20000 cycles 3.5 A 850 VA 380...415 V AC-15 20000 cycles 2.2 A 700 VA 440 V AC-15 20000 cycles 1.5 A 700 VA 500 V AC-15 20000 cycles 1.5 A
Rated operational power in W	180 W 24 V DC-13 1000 cycles 240 W 48 V DC-13 1000 cycles 180 W 60 V DC-13 1000 cycles 140 W 110 V DC-13 1000 cycles 120 W 220 V DC-13 1000 cycles
Height	3.1 in (80 mm)
Width	0.3 in (8.8 mm)
Depth	4.1 in (105 mm)
Net Weight	0.068 lb(US) (0.031 kg)

### Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

### Ordering and shipping details

Category	22366-MAN STR PROTECTORS-GV1/GV3
----------	----------------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Discount Schedule	I11
GTIN	3389110257069
Returnability	No
Country of origin	FR

---

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

---

## Contractual warranty

---

Warranty (in months)	18
----------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

[EU RoHS Directive](#)

Compliant

California proposition 65

**WARNING:** This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.