

Product data sheet

Specifications



ASCO 1900 Load Bank

ASCOLBLV1900

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Capacity Rating 1000...1500 kW

Load Step Resolution 20...25 %

Voltage Rating 400 V AC 50 Hz, 3 phase
480 V AC 60 Hz, 3 phase
600 V AC 60 Hz, 3 phase

Provided Equipment Switch 3 On-Off
LED 1 on
LED 1 error over temperature

Load Tolerance 0...5 %

Ambient Air Temperature -18...122 °F (-28...50 °C)

Surface Finish Polyester powder Gray

Enclosure Material Aluminium
Stainless steel

Environmental

Standards NEMA
ISO 9001

Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer

Lifetime extension

Repair **No**