



Main

Range	ComPact
Product name	ComPact NSX
Range of Product	ComPact NSX100...250
Device short name	NSX100HB1
Product or Component Type	Circuit breaker
Device Application	Motor
Number of poles	3P
Protected poles description	3t
Line Rated Current	25 A 149 °F (65 °C)
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network Frequency	50/60 Hz
Suitability for isolation	Yes EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	85 KA Icu 500 V AC 50/60 Hz IEC 60947-2 80 KA Icu 525 V AC 50/60 Hz IEC 60947-2 75 KA Icu 660/690 V AC 50/60 Hz IEC 60947-2
Performance level	HB1 75 kA 690 V AC
Trip unit name	MA
Trip unit technology	Magnetic
Trip unit protection functions	I
Control Type	Toggle
Circuit breaker mounting mode	Fixed

Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ics] rated service short-circuit breaking capacity	85 KA 500 V AC 50/60 Hz IEC 60947-2 80 KA 525 V AC 50/60 Hz IEC 60947-2 75 KA 660/690 V AC 50/60 Hz IEC 60947-2
Mechanical durability	50000 cycles
Electrical durability	10000 Cycles 690 V In 20000 Cycles 690 V In/2 30000 Cycles 440 V In 50000 cycles 440 V In/2
Mounting Support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	1.38 in (35 mm)
Protection type	I : for short-circuit protection (magnetic)
Trip unit rating	25 A 149 °F (65 °C)
Short-time protection pick-up adjustment type Isd	Adjustable 9 settings
[Isd] Short-time protection pick-up adjustment range	6...14 x In
Earth-leakage protection	Without
Number of slots for electrical auxiliaries	5

Width (W)	4.13 in (105 mm)
Height (H)	6.34 in (161 mm)
Depth (D)	3.39 in (86 mm)
Net Weight	4.52 lb(US) (2.05 kg)

Environment

Standards	EN/IEC 60947
Product Certifications	EAC CCC Marine
Overvoltage category	Class II
Electrical shock protection class	Class II
Pollution degree	3 IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 IEC 62262
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-58...185 °F (-50...85 °C)
Relative humidity	0...95 %
Operating altitude	0...6561.68 ft (0...2000 m) without derating 2000 m...5000 m with derating

Ordering and shipping details

Category	01101-NF...E COMPACT NS IEC CIRCUIT BREAKERS, SWITCHES & MCP'S
Discount Schedule	DE2
GTIN	3606480479182
Returnability	No
Country of origin	PL

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.51 in (14.0 cm)
Package 1 Width	4.33 in (11.0 cm)
Package 1 Length	7.48 in (19.0 cm)
Package 1 Weight	4.02 lb(US) (1.825 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	49.97 lb(US) (22.666 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------