

S201-C40

General Information

Extended Product Type:	S201-C40
Product ID:	2CDS251001R0404
EAN:	4016779464802
Catalog Description:	Miniature Circuit Breaker - S200 - 1P - C - 40 ampere
Long Description:	System pro M compact S200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200 comply with IEC/EN 60898-1, IEC/EN 60947-2, UL1077 and CSA 22.2 No. 235, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200 to save 50% space.

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Miniature Circuit Breakers MCBs



+ Accessories

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85362010

Popular Downloads

Data Sheet, Technical Information: [2CDC002157D0102](#)

Instructions and Manuals: [2CSC400002D0208](#)

Dimensions

Product Net Width: 17.5 mm

Product Net Depth: 69 mm

Product Net Height: 88 mm

Product Net Weight: 0.125 kg

Technical

Standards: IEC/EN 60898-1
IEC/EN 60947-2
UL 1077

Number of Poles: 1

Tripping Characteristic: C

Rated Current (I_n): 40 A

Rated Operational Voltage: acc. to IEC 60898-1 230 / 400 V AC
acc. to IEC 60947-2 230 V AC

Power Loss: 4.8 W
at Rated Operating Conditions per Pole 4.8 W

Rated Insulation Voltage (U_i): acc. to IEC/EN 60664-1 440 V

Operational Voltage: Maximum (Incl. Tolerance) 253 V AC
Maximum (Incl. Tolerance) 72 V DC
Maximum 253 V AC
Maximum 72 V DC
Minimum 12 V AC
Minimum 12 V DC

Rated Frequency (f): 50 Hz
60 Hz

Rated Short-Circuit Capacity (I_{cn}): (230 / 400 V AC) 6 kA

Rated Ultimate Short-Circuit (133 V AC) 20 kA

Breaking Capacity (I_{cu}): (230 V AC) 10 kA

Rated Service Short-Circuit (133 V AC) 15 kA

Breaking Capacity (I_{cs}):

Energy Limiting Class: 3

Overvoltage Category: III

Pollution Degree: 3

Rated Impulse Withstand Voltage (U_{imp}): 4 kV
(6.2 kV @ sea level)
(5.0 kV @ 2000 m)

Dielectric Test Voltage: 50 / 60 Hz, 1 min: 2 kV

Housing Material: Insulation Group II, RAL 7035

Actuator Type: Insulation group II, black, sealable

Contact Position Indication: Red ON / Green OFF

Degree of Protection: IP20

Remarks: IP40 in enclosure with cover

Electrical Endurance: 10000 AC cycle

Mechanical Endurance (N_{endu}): 20000 cycle

Terminal Type: Screw Terminals

Screw Terminal Type: Failsafe Bi-directional Cylinder-lift Terminal

Connecting Capacity:	Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ²
-----------------------------	--

Tightening Torque:	2.8 N·m
---------------------------	---------

Recommended Screw Driver:	Pozidriv 2
----------------------------------	------------

Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
------------------------------	--

Mounting Position:	Any
---------------------------	-----

Environmental

Ambient Air Temperature:	Operation -25 ... +55 °C Storage -40 ... +70 °C
---------------------------------	--

Resistance to Shock acc. to IEC 60068-2-27:	25g / 2 shocks / 13 ms
--	------------------------

Resistance to Vibrations acc. to IEC 60068-2-6:	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
--	--

Environmental Conditions:	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
----------------------------------	---

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

Technical UL/CSA

Maximum Operating Voltage	60 V DC
----------------------------------	---------

UL/CSA:	480Y/277 V AC
----------------	---------------

Connecting Capacity	Busbar 18-8 AWG
----------------------------	-----------------

UL/CSA:	Conductor 18-4 AWG
----------------	--------------------

Tightening Torque UL/CSA:	25 in·lb
----------------------------------	----------

Interrupting Rating acc. to UL1077:	(133 V AC) 6 kA (277 V AC) 6 kA (480Y / 277 V AC) 6 kA (60 V DC) 10 kA
--	---

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CDK403001D0604
--	---------------------------------

Environmental Information:	2CDK400030D0201
-----------------------------------	---------------------------------

Instructions and Manuals:	2CSC400002D0208
----------------------------------	---------------------------------

RoHS Information:	2CDK400003K0201
--------------------------	---------------------------------

Container Information

Package Level 1 Units:	10 piece
-------------------------------	----------

Package Level 1 Width:	92 mm
-------------------------------	-------

Package Level 1 Length:	183 mm
--------------------------------	--------

Package Level 1 Height:	80 mm
--------------------------------	-------

Package Level 1 Gross Weight: 1.295 kg

Package Level 1 EAN: 4016779607117

Package Level 2 Units: 120 piece

Package Level 2 Width: 275 mm

Package Level 2 Length: 395 mm

Package Level 2 Height: 210 mm

Package Level 2 Gross Weight: 14.8 kg

Package Level 2 EAN: 4016779970976

Classifications

Object Classification Code: F

E-nummer: 2100528

ETIM 4: EC000042 - Miniature circuit breaker (MCB)

ETIM 5: EC000042 - Miniature circuit breaker (MCB)

ETIM 6: EC000042 - Miniature circuit breaker (MCB)

ETIM 7: EC000042 - Miniature circuit breaker (MCB)

eClass: 7.0 27141901

UNSPSC: 39121614