

RC unit for 5SL4, 3-pole, type A, In: 63 A, 300 mA, Un AC: 400 V



Model	
product brand name	SENTRON
product designation	RC unit electronic for 5SL4
design of the product	Instantaneous
product version	DI unit, type A, 0.3...63 A, 3P, 300 mA
General technical data	
number of poles	3
size of installation devices according to DIN 43880	1
mechanical service life (operating cycles) typical	10 000
switching function short-term delayed	No
degree of pollution	2
tripping fault current rated value	300 mA
Supply voltage	
supply voltage for testing equipment minimum	125 V
value range of the supply voltage frequency	50 Hz
value range of the supply voltage at AC	230/400 V
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Breaking Capacity	
switching capacity current	
• according to EN 60898 rated value	6 kA
• according to IEC 61008-1 rated value	6 kA
Dissipation	
power loss [W]	
• for rated value of the current at AC in hot operating state per pole	9.6 W
Appearance	
RAL color number	7 035
RAL color number (similar)	7 035
Product details	
product feature silicon-free	Yes
product extension installable supplementary devices	No
Connections	
connectable conductor cross-section solid	
• minimum	0.75 mm ²
• maximum	35 mm ²
connectable conductor cross-section stranded	
• minimum	0.75 mm ²
• maximum	25 mm ²

tightening torque with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m
position of power supply cord	Top, above miniature circuit breaker

Mechanical Design

height	100 mm
width	54 mm
depth	70 mm
installation depth	70 mm
number of modular width units	3
fastening method	Standard rail mounting
mounting position	any
Net Weight	220 g

Environmental conditions

ambient temperature during operation	
• minimum	-25 °C
• maximum	55 °C
ambient temperature during storage minimum	-40 °C
number of test cycles for environmental testing according to IEC 60068-2-30	28

Approvals Certificates

Environment	General Product Approval
-------------	--------------------------

[Environmental Confirmations](#)

[Environmental Confirmations](#)



[Confirmation](#)



General Product Approval	other
--------------------------	-------



[Confirmation](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SM9636-6>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SM9636-6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM9636-6

CAX-Online-Generator



<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>



last modified:

10/9/2025 

