



Catalog No. TC35361SS

Description: 30A 3P DBL THR 4/4X SS 600V NONFUSE

UPC No 783164486254

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Double Throw

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Suitable for use as transfer equipment in standby systems in accordance with Article 702 of the National Electrical Code. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). 60/75 C conductor rating. Full cover interlocks. NEMA 4 X 304 Stainless Steel enclosure. TC35361S



Representative Image

Descriptors

Category	Double Throw
GO Schedule	SB

Specifications

Voltage	600 AC
Amperage	30 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 4/4X Stainless Steel
Wire Range (Cu/Al)	14-2 (Cu/Al)
240 Vac, NEC Std, 3-ph	10.0 hp
480 Vac, NEC Std, 3-ph	20.0 hp
600 Vac, NEC Std, 3-ph	30.0 hp
125 Vdc	3.0 hp
250 Vdc	5.0 hp
GSA Compliance	No

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	25.7 in
Depth	5.5 in
Width	11.9 in
Weight	60.0 lb



