

product type designation



SCALANCE PSP9230PoE power supply

SCALANCE PSP9230PoE; input: 100-240 V AC, 110-250 V DC; output: 24 V DC/1 A + 54 V DC/4 A; IP65 power supply for power-over-Ethernet (PoE); SCALANCE XP208 or XP216 mountable on PSP9230PoE power supply unit; two adapter plates included in scope of supply; operation outside of control cabinet possible; optional accessories: M12 plug (S-coded): 6GK1907-0DC00-6AA4 , M12 plug-in cables pre-assembled (L-coded) lengths 0.5 m to 15 m available (see compact installation instructions)

product brand name

SCALANCE

type of current supply

240 W, input nominal voltage: 100V 240V AC / 110V 250V DC, non-redundant, 50/60 Hz, output: 24V DC (1A) / 54V DC (4A)

Technical Product Detail Page

<https://i.siemens.com/1P6GK5923-0PS00-2AA6>

suitability for use

IP65 power supply unit for PoE, especially for use with SCALANCE XP-200 devices. SCALANCE XP208 can be mounted directly and SCALANCE XP216 can be mounted on the PSP9230PoE using two adapter plates included in scope of delivery. Intended for operation outside a control cabinet.

electrical data

product category

Power supply

electrical data / input

voltage curve / at input

1-phase AC or DC

supply voltage / 1 / rated value

230 V

- supply voltage / 1 / rated value

85 ... 264 V

- type of voltage / 1 / of the supply voltage

AC

- consumed current / 1 / at rated supply voltage / maximum

2.67 A

supply voltage / 2 / rated value

110 V

- supply voltage / 2 / rated value

88 ... 300 V

- type of voltage / 2 / of the supply voltage

DC; PSP9230PoE with EN 50155 supports the voltage range 77 ... 300 V DC

- consumed current / 2 / at rated supply voltage / maximum

2.5 A

design of input / wide range input

Yes

overvoltage category

Category II

buffering time / for rated value of the output current / in the event of power failure / minimum

20 ms

line frequency

- 50 Hz

Yes

- 60 Hz

Yes

line frequency

47 ... 63 Hz

input current / at rated input voltage 230 V / rated value

1.1 A

current limitation / of inrush current / at 25 °C / maximum

60 A

fuse protection type / at input

fuse T 4A, electronically controlled

electrical data / output

voltage curve / at output

Controlled, isolated DC voltage

output voltage

- 1 / at DC / rated value

56 V

- 2 / at DC / rated value

24 V

display version / for normal operation

LED green for DC ok

voltage increase time / of the output voltage / maximum

800 ms

output current

• rated value	3 A
• rated range	0 ... 4 A
supplied active power / typical	224 W
product feature / parallel switching of channels	No
number of parallel-switched equipment resources / for increasing the power	0
efficiency in percent	93.4 %
power loss [W]	24 W
electrical data / closed-loop control	
relative overall tolerance / of the voltage	3 %
residual ripple / maximum	0.05 V
switching frequency	100 kHz; 10...200
electrical data / protection and monitoring	
property of the output / short-circuit proof	Yes
design of short-circuit protection	Electronic shutdown, automatic restart
enduring short circuit current / RMS value / maximum	8.2 A
electrical data / safety	
galvanic isolation / between input and output	Yes
galvanic isolation	Input to output: 4 kV, input to PE 2.5 kV, output to PE: 2.25 kV
operating resource protection class	Class I
interfaces	
number of electrical connections	
• for power supply	1
• for signaling contact	0
type of electrical connection	
• for power supply	M12 (S-coded)
• at output	2x M12 (L-coded)
display version	LED
signal inputs/outputs	
product component / signaling contact	No
design, dimensions and weights	
design	compact
width	280 mm
height	200 mm
depth	65 mm
net weight	4.5 kg
product feature / of the enclosure / housing can be lined up	No
fastening method	wall mounting, back wall mounting
• 19-inch installation	No
• wall mounting	Yes
• screw connection	Yes
ambient conditions	
ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• note	Convection
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
environmental category / according to IEC 60721	Climate class 3K3, without condensation
protection class IP	IP65
standards, specifications, approvals	
standard	
• for safety / from CSA and UL	UL 62368-1:2014 (Second Edition) Report No. E115352, IEC 62368-1:2014 (Second Edition)
• for emitted interference	EN 61000-6-4:2007 +A1:2011
• for interference immunity	EN 61000-6-2:2019
certificate of suitability	EN 61000-6-4: 2007
• CE marking	Yes

• C-Tick • KC approval • IEC 61850-3 • IEEE 1613	Yes Yes No No
MTBF	94.74 a; EN/IEC 61709; 40°C)
accessories	
accessories	power M12 cable connector PRO (6GK1907-0DC00-6AA4)
accessories / included	2 adapter plates including 4 countersunk head screws for mounting SCALANCE XP216 on PSP9230PoE
further information / internet links	
internet link • to website: Selection guide for cables and connectors • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to web page: SiePortal • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/simatic-net https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)
Approvals / Certificates	
General Product Approval	Radio Equipment Type Approval Certificate Railway
    	Confirmation

last modified:

3/10/2026 