

Data sheet for SIMOTICS S-1FL2

Article No. : 1FL2204-2BG11-1MC0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Basic motor data

Motor type	Permanent-magnet synchronous motor, Natural cooling, compact
Motor type	Medium Inertia
Static torque	2.39 Nm
Static current	4.40 A
Maximum torque	8.40 Nm
Maximum current	16.00 A
Maximum speed	6,500 rpm
Rotor moment of inertia	1.2700 kgcm ²
Weight	2.80 kg

Rated data

Rated speed	3,000 rpm
Rated torque	2.39 Nm
Rated current	4.40 A
Rated power	0.75 kW

Encoder system


Encoder system	Absolute encoder 21-bit singleturn + 12-bit multiturn
----------------	---

Motor connection

Connection type	Metal hybrid connector
-----------------	------------------------

Mechanical data

Design acc. to Code I	IM B5 (IM V1, IM V3)
Vibration severity grade	Grade A
Shaft height	40
Flange size (AB)	81 mm
Centering ring (N)	70 mm
Hole circle (M)	90 mm
Screw-on hole (S)	6.6 mm
Overall length (LB)	140.6 mm
Diameter of shaft (D)	19 mm
Length of shaft (E)	40 mm
Length of flange diagonal (P)	104.9 mm
Shaft end	Shaft with parallel key (half-key balancing)
Color of the housing	Anthracite RAL 7016



Holding brake

Rated voltage	24 V DC 10 %
Rated current	0.60 A
Holding torque M _{4Br}	3.30 Nm
Opening time	100 ms
Closing time	15 ms