

# Product datasheet

Specifications



servo motor BSH, Lexium 05,  
3.4N.m, 1500rpm, 100mm,  
untapped shaft, Sincos multi turn,  
with brake, IP65, straight

BSH1001M22F1A

! Discontinued

! Discontinued on: 18 Apr 2024

! To be end-of-service on: 18 Apr 2026

## Main

|                           |  |
|---------------------------|--|
| Device short name         | BSH  |
| Product or component type | Servo motor  |
| Maximum mechanical speed  | 6000 rpm   |
| Continuous stall torque   | 3.4 N.m for LXM05AD14N4, 380...480 V, three phase<br>3.4 N.m for LXM05BD14N4, 380...480 V, three phase<br>3.4 N.m for LXM05CD14N4, 380...480 V, three phase    |
| Peak stall torque         | 7.1 N.m for LXM05AD14N4, 380...480 V, three phase<br>7.1 N.m for LXM05BD14N4, 380...480 V, three phase<br>7.1 N.m for LXM05CD14N4, 380...480 V, three phase    |
| Nominal output power      | 500 W for LXM05AD14N4, 380...480 V, three phase<br>500 W for LXM05BD14N4, 380...480 V, three phase<br>500 W for LXM05CD14N4, 380...480 V, three phase          |
| Nominal torque            | 3.16 N.m for LXM05AD14N4, 380...480 V, three phase<br>3.16 N.m for LXM05BD14N4, 380...480 V, three phase<br>3.16 N.m for LXM05CD14N4, 380...480 V, three phase |
| Nominal speed             | 1500 rpm for LXM05AD14N4, 380...480 V, three phase<br>1500 rpm for LXM05BD14N4, 380...480 V, three phase<br>1500 rpm for LXM05CD14N4, 380...480 V, three phase |
| Product compatibility     | LXM05AD14N4 at 380...480 V three phase<br>LXM05BD14N4 at 380...480 V three phase<br>LXM05CD14N4 at 380...480 V three phase                                     |
| Shaft end                 | Untapped   |
| IP degree of protection   | IP65 standard<br>IP67 with IP67 kit  |
| Speed feedback resolution | 131072 points/turn x 4096 turns  |
| Holding brake             | With   |
| Mounting support          | International standard flange  |
| Electrical connection     | Straight connectors  |

## Complementary

|                          |             |
|--------------------------|-------------|
| Range compatibility      | Lexium 05   |
| supply voltage max       | 480 V       |
| Network number of phases | Three phase |
| Continuous stall current | 1.8 A       |
| maximum continuous power | 1.6 W       |

|  |   |
|--|---|
| <b>Maximum current Irms</b>                  | 6.3 A for LXM05AD14N4<br>6.3 A for LXM05BD14N4<br>6.3 A for LXM05CD14N4                               |
| <b>Maximum permanent current</b>             | 6.3 A   |
| <b>Switching frequency</b>                   | 4 kHz   |
| <b>Second shaft</b>                          | Without second shaft end  |
| <b>Shaft diameter</b>                        | 19 mm   |
| <b>Shaft length</b>                          | 40 mm   |
| <b>Feedback type</b>                         | Multiturn SinCos Hiperface  |
| <b>Holding torque</b>                        | 9 N.m holding brake   |
| <b>Motor flange size</b>                     | 100 mm  |
| <b>Torque constant</b>                       | 1.83 N.m/A at 120 °C  |
| <b>Back emf constant</b>                     | 115 V/krpm at 120 °C  |
| <b>Number of motor poles</b>                 | 8   |
| <b>Rotor inertia</b>                         | 2.018 kg.cm <sup>2</sup>  |
| <b>Stator resistance</b>                     | 13.9 Ohm at 20 °C   |
| <b>Stator inductance</b>                     | 64.3 mH at 20 °C  |
| <b>Stator electrical time constant</b>       | 4.63 ms at 20 °C  |
| <b>Maximum radial force Fr</b>               | 530 N at 5000 rpm<br>570 N at 4000 rpm<br>630 N at 3000 rpm<br>720 N at 2000 rpm<br>900 N at 1000 rpm |
| <b>Maximum axial force Fa</b>                | 0.2 x Fr  |
| <b>Brake pull-in power</b>                   | 18 W  |
| <b>Type of cooling</b>                       | Natural convection  |
| <b>Length</b>                                | 199.5 mm  |
| <b>Centring collar diameter</b>              | 95 mm   |
| <b>Centring collar depth</b>                 | 3.5 mm  |
| <b>Number of mounting holes</b>              | 4   |
| <b>Mounting holes diameter</b>               | 9 mm  |
| <b>Circle diameter of the mounting holes</b> | 115 mm  |
| <b>Net weight</b>                            | 4.8 kg  |
| <b>Sizing reference</b>                      | BSH1001M  |
| <b>Network number of phases</b>              | 3   |
| <b>Accuracy error [angular]</b>              | 1.4 °   |
| <b>Temperature copper hot</b>                | 120 °C  |
| <b>Temperature magnet hot</b>                | 100 °C  |
| <b>Temperature magnet rt</b>                 | 20 °C   |

## Packing Units

|                                     |     |
|-------------------------------------|-----|
| <b>Unit Type of Package 1</b>       | PCE |
| <b>Number of Units in Package 1</b> | 1   |

# Contractual warranty

---

Warranty (in months)

18



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No