



Modular residual current protective device LCD, 230V AC IDN 0.03A-3A (type A)  
German=INS-10 sec (SEL)

Model	
product brand name	SENTRON
product designation	modular residual current device
design of the product	Digital, type A
adjustable response delay time	
• initial value	0.02 s
• full-scale value	10 s
frequency of the measuring circuit rated value	
• minimum	50 Hz
• maximum	60 Hz
protection class IP at connection all terminals	IP20
type of connectable summation current transformer	5SV8702-0KK, 5SV8703-0KK, 5SV8704-0KK, 5SV8705-0KK, 5SV8706-0KK
overvoltage category	III
degree of pollution	2
type of voltage of the operating voltage for actuation	AC
operating voltage	
• rated value minimum	184 V
• rated value maximum	276 V
• at AC rated value	230 V
protection class IP on the front	IP41
Dissipation	
power loss [V·A] maximum	6 VA
Main circuit	
operating frequency rated value	
• minimum	50 Hz
• maximum	60 Hz
Auxiliary circuit	
number of CO contacts for auxiliary contacts	2
Relay contacts	
switching voltage of relay contacts rated value	230 V
switching current of relay contacts rated value	6 A
Product function	
product function	
• residual current display	Yes
• error memory	Yes
• communication function	No

Connections	
product component removable terminal for main circuit	No
product component removable terminal for auxiliary and control circuit	No
wire length to the summation current transformer	10 m
<b>stripped length</b>	10 mm
<b>connectable conductor cross-section for flexible conductor</b>	
• minimum	0.13 mm <sup>2</sup>
• maximum	2.1 mm <sup>2</sup>
<b>connectable conductor cross-section for rigid conductor</b>	
• minimum	0.13 mm <sup>2</sup>
• maximum	2.1 mm <sup>2</sup>
<b>tightening torque with screw-type terminals</b>	
• minimum	0.5 N·m
• maximum	0.6 N·m
<b>type of connectable conductor cross-sections for AWG cables for supply voltage</b>	AWG 26 ... AWG 14
<b>type of electrical connection</b>	screw terminal

Mechanical Design	
<b>height</b>	85 mm
<b>width</b>	54 mm
<b>depth</b>	68 mm
<b>fastening method</b>	DIN rail
<b>Net Weight</b>	269 g

Environmental conditions	
<b>influence of the surrounding temperature</b>	Max. 95% humidity
<b>ambient temperature during operation</b>	
• minimum	-10 °C
• maximum	50 °C
<b>ambient temperature during storage</b>	
• minimum	-20 °C
• maximum	70 °C

Certificates	
<b>reference code according to IEC 81346-2</b>	F

Approvals Certificates	
<b>Environment</b>	General Product Approval

[Environmental Con-  
firmations](#)



[Environmental Con-  
firmations](#)



[Confirmation](#)

General Product Approval

other



[Miscellaneous](#)

[Confirmation](#)



### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV8101-6KK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV8101-6KK>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SV8101-6KK](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV8101-6KK)

**CAX-Online-Generator**

<https://www.siemens.com/cax>

**Tender specifications**

<https://www.siemens.com/specifications>

**Characteristic curves**

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

---

last modified:

3/18/2026 

