

SIMATIC IPC 477E 22" Touch (1920 x 1080); Neutral front with USB; (front); 4 USB (back), Ethernet (10/100/1000); XEON E3-1505L; 3x Gbit Ethernet (IE/PN); 16 GB; without RS 232/RS485; without PCIe; Windows 10 IoT Enterprise 2016 LTSB (64-bit) for Xeon; Without replaceable mass storage; 240 GB solid-state drive SATA Without SIMATIC software; 24 V DC industrial power supply

| General information                                       |                                                                                                                                                                                                            |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product type designation                                  | IPC477E                                                                                                                                                                                                    |
| Installation type/mounting                                |                                                                                                                                                                                                            |
| Mounting                                                  | For horizontal and vertical mounting                                                                                                                                                                       |
| Design                                                    | Panel PC, built-in unit                                                                                                                                                                                    |
| Supply voltage                                            |                                                                                                                                                                                                            |
| Type of supply voltage                                    | 100/240 V AC (autorange) 50/60 Hz; optional 24 V DC                                                                                                                                                        |
| Rated value (DC)                                          | 24 V; PELV / SELV floating                                                                                                                                                                                 |
| Line frequency                                            |                                                                                                                                                                                                            |
| • Rated value 50 Hz                                       | Yes                                                                                                                                                                                                        |
| • Rated value 60 Hz                                       | Yes                                                                                                                                                                                                        |
| Mains buffering                                           |                                                                                                                                                                                                            |
| • Mains/voltage failure stored energy time                | 20 ms                                                                                                                                                                                                      |
| Processor                                                 |                                                                                                                                                                                                            |
| Processor type                                            | Celeron G3902 (2C/2T, 1.6 GHz, 2 MB Cache); Core i3-6102E (2C/4T, 1.9 GHz, 3 MB Cache); Core i5-6442EQ (4C/4T, 1.9 (2.7) GHz, 6 MB Cache, iAMT); Xeon E3-1505L v5 (4C/8T, 2.0 (2.8) GHz, 8 MB Cache, iAMT) |
| Chipset                                                   | Intel C236 / Intel H110                                                                                                                                                                                    |
| Graphic                                                   |                                                                                                                                                                                                            |
| Graphics controller                                       | Intel HD graphics controller                                                                                                                                                                               |
| Drives                                                    |                                                                                                                                                                                                            |
| Hard disk                                                 | 2.5" SATA ≥ 320 GB                                                                                                                                                                                         |
| SSD                                                       | Yes; 128 / 240 / 480 GB                                                                                                                                                                                    |
| Storage                                                   |                                                                                                                                                                                                            |
| Type of memory                                            | DDR4-2400 SO-DIMM                                                                                                                                                                                          |
| Main memory                                               | 4 / 8 / 16 GB, ECC optional                                                                                                                                                                                |
| Capacity of main memory, max.                             | 16 Gbyte                                                                                                                                                                                                   |
| Data areas and their retentivity                          |                                                                                                                                                                                                            |
| Retentive data area (incl. timers, counters, flags), max. | 512 kbyte; 128 KB can be stored in the buffer time; optional                                                                                                                                               |
| Hardware configuration                                    |                                                                                                                                                                                                            |
| Slots                                                     |                                                                                                                                                                                                            |
| • free slots                                              | 1x PCIe (slot with card retainer), 1x slot for CFAST card                                                                                                                                                  |
| • Number of PCI slots                                     | 1; Optional                                                                                                                                                                                                |
| • Number of compact flash slots                           | 1; CFAST                                                                                                                                                                                                   |
| Interfaces                                                |                                                                                                                                                                                                            |
| Number of industrial Ethernet interfaces                  | 3; 3x Ethernet (RJ45)                                                                                                                                                                                      |
| USB port                                                  | 4x USB 3.0                                                                                                                                                                                                 |
| Connection for keyboard/mouse                             | USB / USB                                                                                                                                                                                                  |
| Video interfaces                                          |                                                                                                                                                                                                            |
| • Graphics interface                                      | 2x DisplayPort                                                                                                                                                                                             |
| Industrial Ethernet                                       |                                                                                                                                                                                                            |
| • Industrial Ethernet interface                           | 3x Ethernet (RJ45)                                                                                                                                                                                         |
| — 100 Mbps                                                | Yes                                                                                                                                                                                                        |
| — 1000 Mbps                                               | Yes                                                                                                                                                                                                        |
| Interrupts/diagnostics/status information                 |                                                                                                                                                                                                            |
| Bus diagnostics                                           | Yes                                                                                                                                                                                                        |
| Integrated Functions                                      |                                                                                                                                                                                                            |

|                                                                            |                                                                                                                                 |
|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>Monitoring functions</b>                                                |                                                                                                                                 |
| • Temperature monitoring                                                   | Yes                                                                                                                             |
| • Watchdog                                                                 | Yes                                                                                                                             |
| • Fan                                                                      | No                                                                                                                              |
| • Monitoring function via network                                          | Optional                                                                                                                        |
| <b>EMC</b>                                                                 |                                                                                                                                 |
| <b>Interference immunity against discharge of static electricity</b>       |                                                                                                                                 |
| • Interference immunity against discharge of static electricity            | ±6 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2                                        |
| <b>Interference immunity against high-frequency electromagnetic fields</b> |                                                                                                                                 |
| • Interference immunity against high frequency radiation                   | 10 V/m, 80 ... 2 000 MHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m, 2 ... 2.7 GHz; 10 V, 10 kHz ... 80 MHz acc. to IEC 61000-4-6    |
| <b>Interference immunity to cable-borne interference</b>                   |                                                                                                                                 |
| • Interference immunity on supply cables                                   | ±2 kV acc. to IEC 61000-4-4, burst; ±1 kV acc. to IEC 61000-4-5, surge symmetric; ±2 kV acc. to IEC 61000-4-5, surge asymmetric |
| • Interference immunity on signal cables >30m                              | ±2 kV acc. to IEC 61000-4-5, surge, length > 30 m                                                                               |
| • Interference immunity on signal cables < 30m                             | ±1 kV acc. to IEC 61000-4-4; burst; length < 3 m; ±2 kV acc. to IEC 61000-4-4; burst; length > 3 m                              |
| <b>Interference immunity against voltage surge</b>                         |                                                                                                                                 |
| • asymmetric interference                                                  | ±2 kV acc. to IEC 61000-4-5, surge asymmetric                                                                                   |
| • symmetric interference                                                   | ±1 kV acc. to IEC 61000-4-5, surge symmetric                                                                                    |
| <b>Interference immunity to magnetic fields</b>                            |                                                                                                                                 |
| • Interference immunity to magnetic fields at 50 Hz                        | 100 A/m; to IEC 61000-4-8                                                                                                       |
| <b>Emission of conducted and non-conducted interference</b>                |                                                                                                                                 |
| • Interference emission via line/AC current cables                         | EN 61000-6-3, EN 61000-6-4, CISPR 22 Class B, FCC Class A                                                                       |
| <b>Degree and class of protection</b>                                      |                                                                                                                                 |
| IP (at the front)                                                          | IP65                                                                                                                            |
| IP (rear)                                                                  | IP20                                                                                                                            |
| <b>Standards, approvals, certificates</b>                                  |                                                                                                                                 |
| CE mark                                                                    | Yes                                                                                                                             |
| CSA approval                                                               | Yes                                                                                                                             |
| UL approval                                                                | Yes                                                                                                                             |
| • UL 508                                                                   | Yes                                                                                                                             |
| cULus                                                                      | Yes                                                                                                                             |
| RCM (formerly C-TICK)                                                      | Yes                                                                                                                             |
| KC approval                                                                | Yes                                                                                                                             |
| EAC (formerly Gost-R)                                                      | Yes                                                                                                                             |
| FCC                                                                        | Yes                                                                                                                             |
| EMC                                                                        | CE, EN 61000-6-4; CISPR 22:2004 Class A; FCC Class A                                                                            |
| <b>Use in hazardous areas</b>                                              |                                                                                                                                 |
| • ATEX Zone 2                                                              | Yes; for inscription on device rating plate                                                                                     |
| • ATEX Zone 22                                                             | Yes; for inscription on device rating plate                                                                                     |
| • IECEx Zone 2                                                             | Yes; for inscription on device rating plate                                                                                     |
| • IECEx Zone 22                                                            | Yes; for inscription on device rating plate                                                                                     |
| • CCC Ex                                                                   | Yes; for inscription on device rating plate                                                                                     |
| • cULus Class I Zone 1                                                     | No                                                                                                                              |
| • cULus Class I Zone 2, Division 2                                         | Yes; for inscription on device rating plate                                                                                     |
| • cULus Class II Division 2                                                | Yes; for inscription on device rating plate                                                                                     |
| • FM Class I Division 2                                                    | No                                                                                                                              |
| • FM Class II Division 2                                                   | No                                                                                                                              |
| <b>Marine approval</b>                                                     |                                                                                                                                 |
| • Germanischer Lloyd (GL)                                                  | Yes                                                                                                                             |
| • American Bureau of Shipping (ABS)                                        | Yes                                                                                                                             |
| • Bureau Veritas (BV)                                                      | Yes                                                                                                                             |
| • Det Norske Veritas (DNV)                                                 | Yes                                                                                                                             |
| • Korean Register of Shipping (KRS)                                        | Yes                                                                                                                             |
| • Lloyds Register of Shipping (LRS)                                        | Yes                                                                                                                             |
| • Nippon Kaiji Kyokai (Class NK)                                           | Yes                                                                                                                             |
| <b>Ambient conditions</b>                                                  |                                                                                                                                 |
| Ambient temperature during operation                                       |                                                                                                                                 |

|                                                               |                                                                                                                                                                             |
|---------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • min.                                                        | 0 °C                                                                                                                                                                        |
| • max.                                                        | 45 °C                                                                                                                                                                       |
| Ambient temperature during storage/transportation             |                                                                                                                                                                             |
| • min.                                                        | -20 °C                                                                                                                                                                      |
| • max.                                                        | 60 °C                                                                                                                                                                       |
| Relative humidity                                             |                                                                                                                                                                             |
| • Relative humidity                                           | Tested according to IEC 60068-2-78, IEC 60068-2-30: 5% to 80% at 25 °C (no condensation)                                                                                    |
| Vibrations                                                    |                                                                                                                                                                             |
| • Vibration resistance during operation acc. to IEC 60068-2-6 | IEC 60068-2-6; 5 Hz to 9 Hz: 3.5 mm; 9 Hz to 500 Hz: 9.8 m/s <sup>2</sup> (with SSD or CFast); 10 Hz to 58 Hz: 0.0375 mm; 58 Hz to 200 Hz: 4.9 m/s <sup>2</sup> (hard disk) |
| Shock testing                                                 |                                                                                                                                                                             |
| • Shock load during operation                                 | IEC 60068-2-27; 150 m/s <sup>2</sup> , 11 ms (without hard disk); 50 m/s <sup>2</sup> , 30 ms (with hard disk)                                                              |
| Operating systems                                             |                                                                                                                                                                             |
| pre-installed operating system                                | Windows 7 Ultimate (Multi-Language) 64-bit, Windows Embedded Standard 7 E/P 32-bit / 64-bit, Windows 10                                                                     |
| without operating system                                      | Yes; Optional                                                                                                                                                               |
| pre-installed operating system                                |                                                                                                                                                                             |
| • Windows 7                                                   | Yes; Ultimate 64 bit                                                                                                                                                        |
| • Windows 10 Enterprise                                       | Yes; Windows 10 Enterprise 2016 LTSC, 64 bit, MUI                                                                                                                           |
| Software                                                      |                                                                                                                                                                             |
| SIMATIC Software                                              | Optionally with pre-installed SIMATIC WinCC RT Advanced / Software Controller CPU 1500S software bundle                                                                     |
| Approvals / Certificates                                      |                                                                                                                                                                             |
| General Product Approval                                      |                                                                                                                                                                             |
| Maritime application                                          |                                                                                                                                                                             |

[Miscellaneous](#)



[BIS CRS](#)

[China RoHS](#)



|                                                                                     |                                          |                                             |                                             |
|-------------------------------------------------------------------------------------|------------------------------------------|---------------------------------------------|---------------------------------------------|
| Maritime application                                                                | Dangerous goods                          |                                             |                                             |
|  | <a href="#">NK / Nippon Kaiji Kyokai</a> | <a href="#">Test Summary Report UN 38.3</a> | <a href="#">Dangerous goods information</a> |

last modified:

11/20/2025 