

! If you have questions regarding login with Siemens ID, please check the [FAQ](#).

SiePortal

The integrated platform for your informatio workflow – bringing together Industry Mall

SiePortal | Region and language | Contact | Help | Support Request

Search for products

> Home > Catalogue > ... > ... > Pressure transmitters > Single-range transmitters > SITRANS P220 > 7MF1567-3BG00-1AA1

Products & Services

Support

7MF1567-3BG00-1AA1



Image similar

SITRANS P220 Transmitters for pressure and absolute pressure fully welded version for high-pressure and refrigerant applications Non-linearity: 0.25 Percent (typically) wetted parts material: stainless steel; non-wetted parts material: stainless steel Measuring range for gauge: 0 to 6 bar, Overload- pressure 15 bar Output signal: 4 to 20 mA two-wire connection, power supply DC 7 to 33 V without explosion protection Electrical connection: plug to DIN EN 175301-803-A, thread for packed gland M16 (with connector) Process connection: G1/2" male to EN 837-1 (1/2" BSP male) (standard for metric pressure ranges mbar, bar) Standard version

List Price	Show prices
Customer Price	Show prices
Additional Services	For this product we can offer Services like Spare Part Delivery/Repair/Exchange. You have currently no rights to enter the Service Web Shop for that. For further information & to order this service, please contact your local Spares&Repair Partner
	For this product we can offer extended warranty contracts EEO (material exchange for a single product) OEM RSC (Repair Service Contract for a whole machine) For further information & to order these services, please contact your local Siemens Service Partner
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	7MF1567-3BG00-1AA1
Product Description	SITRANS P220 Transmitters for pressure and absolute pressure fully welded version for high-pressure and refrigerant applications Non-linearity: 0.25 Percent (typically) wetted parts material: stainless steel; non-wetted parts material: stainless steel Measuring range for gauge: 0 to 6 bar, Overload- pressure 15 bar Output signal: 4 to 20 mA two-wire connection, power supply DC 7 to 33 V without explosion protection Electrical connection: plug to DIN EN 175301-803-A, threat for packed gland M16 (with connector) Process connection: G1/2" male to EN 837-1 (1/2" BSP male) (standard for metric pressure ranges mbar, bar) Standard version Standard version

Product family	SITRANS P220
Product Lifecycle (PLM)	PM300:Active Product

Price data

Price Group / Headquarter Price Group	8P4
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Delivery information

Export Control Regulations	ECCN : N / AL : N
Estimated dispatch time (Working Days)	1 Day/Days
Net Weight (kg)	0.200 Kg
Packaging Dimension	90.00 x 149.00 x 42.00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	4047623602781
UPC	Not available
Commodity Code	90262020
LKZ_FDB/ CatalogID	F101-1
Product Group	4778
Group Code	R3P0
Country of origin	Switzerland
Compliance with the substance restrictions according to RoHS directive	Since: 20/07/17
Product class	A: Standard product which is a stock item could be returned within the returns guidelines/period.
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	Yes
SCIP number	Not available

Classifications

	Version	Classification
eClass	12	27-20-06-14

eClass	14	27-20-06-14
eClass	6	27-20-06-14
eClass	7.1	27-20-06-14
eClass	8	27-20-06-14
eClass	9	27-20-06-14
eClass	9.1	27-20-06-14
ETIM	7	EC002990
ETIM	8	EC002990
ETIM	9	EC002990
UNSPSC	15	32-15-17-03

: