

Modular Metering Meter Mod III

Meter Stack Modules
Single-Phase
Plus Accessories
Product Features

- UL listed
- 800 amp, 4-wire cross bus (aluminum), except where noted below.
- Ring-type and Ringless Sockets
- Front Accessible Field Phase Balancing by Meter Module
- (1) 14-4 Equipment Ground per Socket, Factory Installed

Ring Type Socket

Socket Amps	No. of Sockets	Product Number
125A	2	TMP8212R
125A	3	TMP8312R
125A	4	TMP8412R
125A	5	TMP8512R
125A	6	TMP8612R
200A	2	TMP8220R
200A	3	TMP8320R
200A	4	TMP8420R
200A	5	TMP8520R
200A	5	TMP8520RBUS

One snap-type, aluminum sealing ring (TSR5) per socket included.

Ringless Type Socket (Includes 5th Jaw Standard)¹

Socket Amps	No. of Sockets	Product Number
125A	2	TMPR8212R
125A	3	TMPR8312R
125A	4	TMPR8412R
125A	5	TMPR8512R
125A	6	TMPR8612R
200A	2	TMPR8220R
200A	3	TMPR8320R
200A	4	TMPR8420R
200A	5	TMPR8520R
200A	5	TMPR8520RHBUS
200A	5	TMPR8520RHB ²
200A	5	TMPR8520RHBBS ²

Product Features

- UL listed
- 1200 amp, 4-wire cross bus (aluminum)
- Ring-type and Ringless Sockets
- Front Accessible Field Phase Balancing by Meter Module
- (1) 14-4 Equipment Ground per Socket, Factory Installed

Ring-Type Socket

Socket Amps	No. of Sockets	Product Number
125A	2	TMP12212R
125A	3	TMP12312R
125A	4	TMP12412R
125A	5	TMP12512R
125A	6	TMP12612R
200A	2	TMP12220R
200A	3	TMP12320R
200A	4	TMP12420R
200A	5	TMP12520R
200A	5	TMP12520RBUS

Ringless Type Socket (Includes 5th Jaw Standard)¹

Socket Amps	No. of Sockets	Product Number
125A	2	TMPR12212R
125A	3	TMPR12312R
125A	4	TMPR12412R
125A	5	TMPR12512R
125A	6	TMPR12612R
125A	2	TMPR12212RHB
125A	3	TMPR12312RHB
125A	4	TMPR12412RHB
125A	5	TMPR12512RHB
125A	6	TMPR12612RHB
200A	2	TMPR12220R
200A	3	TMPR12320R
200A	4	TMPR12420R
200A	5	TMPR12520R
200A	5	TMPR12520RHB
200A	5	TMPR12520RHBUS
200A	2	TMPR12220RHB
200A	3	TMPR12320RHB
200A	4	TMPR12420RHB

Section 2



TMP8512R

TMP8220R

Ring Type Socket Factory Phase Balanced (w/Copper Bus)

Socket Amps	No. of Sockets	Product Number
125A	2	TMP8212RAB
125A	2	TMP8212RAC
125A	2	TMP8212RBC
125A	3	TMP8312RAB
125A	3	TMP8312RAC
125A	3	TMP8312RBC
125A	4	TMP8412RAB
125A	4	TMP8412RAC
125A	4	TMP8412RBC

Tenant Main Circuit Breakers 10,000 AIC

Socket Amps	Ampere Rating	Wire Size Load Lugs	Product Number
125	60	(1) #8-#3 CU; #8-#3 AL	THQL2160
125	70	(1) #6-1/0 CU; #4-#1/0 AL	THQL2170
125	80	(1) #6-1/0 CU; #4-#1/0 AL	THQL2180
125	90	(1) #6-1/0 CU; #4-#1/0 AL	THQL2190
125	100	(1) #2-2/0 CU; #2-2/0 AL	THQL21100
125	110		THQL21110
125	125	(1) #2-2/0 CU; #2-2/0 AL	THQL21125
125	125		TMQL21125SF ³
200	100	(1) #1-3/0 CU; #1-3/0 AL	TQD22100
200	125	(1) #1-3/0 CU; #1-3/0 AL	TQD22125
200	150	(1) #1-3/0 CU; #1-3/0 AL	TQD22150
200	175	(1) #1-3/0 CU; #1-3/0 AL	TQD22175
200	200	(1) #1-3/0 CU; #1-3/0 AL	TQD22200
200	225		Use TMQD

Tenant Main Circuit Breakers 22,000 AIC

Socket Amps	Ampere Rating	Wire Size Load Lugs	Product Number
125	60	(1) #8-3 CU; #8-2 AL	THHQL2160
125	70	(1) #6-1/0 CU; (1) #4 1/0	THHQL2170
125	80	(1) #6-1/0 CU; #4-1/0 AL	THHQL2180
125	90	(1) #6-1/0 CU; #4-1/0 AL	THHQL2190
125	100	(1) #6-1/0 CU; #4-1/0 AL	THHQL21100
125	110		THHQL21110
125	125	(1) #2-2/0 CU; #2-2/ AL	THHQL21125
200	100	(1) #1-3/0 CU; #1-3/0 AL	THQD22100
200	125	(1) #1-3/0 CU; #1-3/0 AL	THQD22125
200	150	(1) #1-3/0 CU; #1-3/0 AL	THQD22150
200	175	(1) #1-3/0 CU; #1-3/0 AL	THQD22175
200	200	(1) #1-3/0 CU; #1-3/0 AL	THQD22200
200	225		Use TMQD

Tenant Main Circuit Breakers 42,000 AIC

Socket Amps	Ampere Rating	Wire Size Load Lugs	Product Number
125	60	(1) #10-1/0 CU; #10-1/0 AL	TMQL2160
125	70	(1) #10-1/0 CU; #10-1/0 AL	TMQL2170
125	80	(1) #10-1/0 CU; #10-1/0 AL	TMQL2180
125	90	(1) #10-1/0 CU; #10-1/0 AL	TMQL2190
125	100	(1) #10-1/0 CU; #10-1/0 AL	TMQL21100
125	125	(1) #10-1/0 CU; #10-1/0 AL	TMQL21125

Tenant Main Circuit Breakers 100,000 AIC

Socket Amps	Ampere Rating	Wire Size Load Lugs	Product Number
200	60	(1) #6-1/0 CU; #6-1/0 AL	TMQD22060
200	70	(1) #6-1/0 CU; #6-1/0 AL	TMQD22070
200	80	(1) #6-1/0 CU; #6-1/0 AL	TMQD22080
200	90	(1) #6-1/0 CU; #6-1/0 AL	TMQD22090
200	100	(1) #6-4/0 CU; #6-4/0 AL	TMQD22100
200	125	(1) #6-4/0 CU; #6-4/0 AL	TMQD22125
200	150	(1) #6-4/0 CU; #6-4/0 AL	TMQD22150
200	175	(1) #6-4/0 CU; #6-4/0 AL	TMQD22175
200	200	(1) #6-4/0 CU; #6-4/0 AL	TMQD22200
200	225	(1) #6-4/0 CU; #6-4/0 AL	TMQD22225

¹Available with factory installed horn-type by-pass. Add HB suffix to Product Number. Includes factory installed fifth jaw.

²Includes horn by-pass.

³Sub-feed lug, no overcurrent protection.

