

Product data sheet

Specifications



ASCO 5900 Load Bank

ASCOLBLV5900

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

| | |
|-------------------------|---|
| Voltage Rating | 480 V AC 60 Hz, 3 phase 240/480 V AC 60 Hz, 3 phase |
| Capacity Rating | 2500 kW 2000 kW 1000 kW |
| Load Step Resolution | 5 kW |
| Cooling System Rating | 24237321.6 Gal/hr(US) (91746.6 m3/h) |
| Provided Equipment | Switch 3 On-Off LED 2 on LED 1 alarm indication Multi-function meter 1 |
| Ambient Air Temperature | -18...122 °F (-28...50 °C) |
| Enclosure Material | Aluminium Steel |
| Surface Finish | Polyester powder Gray |
| Terminal Connections | Quick |
| Width | 9.6 in (243 mm) |
| Length | 224.0 in (5689 mm) |
| Height | 122.008 in (3099 mm) |
| Product Weight | 6600.6 lb(US) (2994 kg) |

Environmental

Standards ISO 9001
NEMA

Packing Units

| | |
|------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 6600.6 lb(US) (2994 kg) |

Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

| | |
|--|-----|
| Packaging made with recycled cardboard | Yes |
|--|-----|

| | |
|--------------------------------------|----|
| Packaging without single use plastic | No |
|--------------------------------------|----|

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|