


Product datasheet

Specifications



function module, TransferPacT, load shedding and availability warning, output signal

TPCDIO05

Main

Range of product	TransferPacT
Product or component type	I/O module
Device application	Signalling

Complementary

Auxiliary contact composition	2 NO + 1 NC
Signalling function	Load-shedding indication Output status
Auxiliary connection terminal	Screw clamp terminal 0.05...2.6 mm²
Mounting mode	Plug-in
Mounting position	Left-bottom
[Ui] rated insulation voltage	300 V AC
Tightening torque	0.6 N.m +/- 0.1 N.m
Height	56.5 mm
Width	20 mm
Depth	69 mm
Net weight	40 g
Accessory / separate part category	Signalling accessory

Environment

IP degree of protection	IP20
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	10.5 cm
Package 1 Length	11 cm
Package 1 Weight	110 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.38 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	Cbd5c90f-9537-4f0e-b5dd-d4cb5b67b442
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	58
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins