


# Product datasheet

Specifications



## Add-on contact block, TeSys Deca Frame 2/3, 1NC+1NO(fault), front, spring terminal, for GV2/GV3(except GV3ME)

GVAED0113

### Main

Range	TeSys TeSys Deca
Device short name	GVAED
Product or component type	Auxiliary contact block
Product compatibility	GV3P GV3L
Mounting location	Front side
Auxiliary contacts operation	Fault signal 1 NO
Pole contact composition	1 NO + 1 NC
Quantity per set	Set of 1

### Complementary

[U <sub>i</sub> ] rated insulation voltage	600 V conforming to UL 508 690 V conforming to IEC 60947-1 600 V conforming to CSA C22.2 No 14
[U <sub>e</sub> ] rated operational voltage	24...240 V AC 24...60 V DC
[I <sub>th</sub> ] conventional free air thermal current	2.5 A
Mechanical durability	100000 cycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Protection type	GB2CB... circuit breaker GG fuse 10 A
Rated operational power in VA	300 VA at 48 V AC-15 - electrical durability: 100000 cycles 400 VA at 690 V AC-15 - electrical durability: 100000 cycles 500 VA at 110...127 V AC-15 - electrical durability: 100000 cycles 500 VA at 500 V AC-15 - electrical durability: 100000 cycles 650 VA at 440 V AC-15 - electrical durability: 100000 cycles 720 VA at 230...240 V AC-15 - electrical durability: 100000 cycles 850 VA at 380...415 V AC-15 - electrical durability: 100000 cycles
Rated operational power in W	120 W at 240 V DC-13 - electrical durability: 100000 cycles 140 W at 110 V DC-13 - electrical durability: 100000 cycles 140 W at 24 V DC-13 - electrical durability: 100000 cycles 180 W at 60 V DC-13 - electrical durability: 100000 cycles 240 W at 48 V DC-13 - electrical durability: 100000 cycles
Height	13 mm
Width	44.5 mm
Depth	31.5 mm

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

---

<b>Net weight</b>	0.05 kg
-------------------	---------

---

<b>Colour</b>	Dark grey
---------------	-----------

---

## Environment

---

<b>Environmental characteristic</b>	Normal environment
-------------------------------------	--------------------

---

<b>Standards</b>	EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 IEC/EN 60335-1:Clause 30.2 IEC/EN 60335-2-40:Annex JJ
------------------	--

---

<b>Product certifications</b>	CB Scheme CE UKCA CCC cULus EAC
-------------------------------	--

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	6.400 cm
-------------------------	----------

---

<b>Package 1 Width</b>	7.500 cm
------------------------	----------

---

<b>Package 1 Length</b>	13.100 cm
-------------------------	-----------

---

<b>Package 1 Weight</b>	36.000 g
-------------------------	----------

---

## Contractual warranty

---

<b>Warranty (in months)</b>	18
-----------------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	0.2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	42
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins