



Figure similar

MAINS CHOKE F.FU; PHASES:3; UN1(V):575; ITHMAX 1(A) / F1(HZ):129 /60; I LN (A):116; UK(%):5; LN(MH):0,34; TA/ISOKL:40 /H; IP00; TYPE OF TERMINALS:FLAT-TYPE TERMINAL; EN 61558-2-20 >UL/CSA-RECOGNIZED< >CHOKE<

General technical data		
product designation		Netzdrossel f. FU
phase number		3
type of voltage		AC
operating voltage rated value	V	575
operating frequency rated value	Hz	60
•		
— operational current at AC rated value	A	116
— current at AC maximum	A	129
inductivity rated value	H	0.00034
relative inductive drop in voltage for rated value of the current, voltage and frequency	%	5
power loss [W] of the coil	W	217
power loss [W] of the iron core	W	176
Mechanical data		
type of electrical connection for main current circuit		flat connector
width	m	0.3
height	m	0.269
depth	m	0.221
Ambient conditions		
thermal class according to IEC 60085		H
ambient temperature rated value	°C	40
protection class IP		IP00
Certificates/ approvals		
General Product Approval	other	Environment



[Confirmation](#)



[Environmental Confirmations](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
 Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4EU3022-0ER00-0AA0>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EU3022-0ER00-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4EU3022-0ER00-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EU3022-0ER00-0AA0&lang=en

last modified:

8/8/2025 