



TD500 test device incl. 2 connecting cables PC-TD500, 3VA-TD500 external power supply accessory for: 3VA6

Model	
product brand name	SETRON
product designation	Test device
accessories	Test device
General technical data	
mounting position	any
protection class IP	IP30
Current	
number of circuit breakers / directly connectable	1
Mechanical Design	
height	190 mm
width	105 mm
depth	42 mm
Net Weight	1.035 kg
Connections according UL	
ambient temperature / during operation	
• minimum	-10 °C
• maximum	40 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
Certificates	
General Product Approval	EMV

[Miscellaneous](#)



[Confirmation](#)



Test Certificates	Maritime application	other		Dangerous goods	Environment
Type Test Certificates/Test Report		Miscellaneous	Confirmation	Dangerous goods information	Environmental Confirmations

Environment

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9977-0MB10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9977-0MB10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9977-0MB10

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>



last modified:

4/3/2025

